

40602

LOG OF BORING MW-8

Project: Wonderworld Phase II
 Project Number: 276.0012
 Site Geologist: John Pyle
 Drilling Company: Converse Consultants
 Drill Rig: BK B-61
 Drilling Method: Auger

Date Drilled: 7/19/00
 Elevations:
 Surfaces: NS
 Top of Casing: 2213.07
 Standup Pipe: NS
 Static Water: 2196.94

Depth (Feet)	Lab. Sample	PID (ppm)	Moisture	Odor	Lith. Sample Int.	Graphic Log	Lithologic Description	Well Completion Detail
2							FILL - Asphalt, with cobbles, dry, light brown.	2" PVC Blank Casing
4							CL - Sandy clay with gravel, dry to moist, light brown.	Cement Slurry (0'-7')
6							Caliche - dry.	
8							CL - Clay with silt, caliche gravel, dry, light brown	
10							Caliche - dry	
12							CL - Lean Clay, dry to moist, light brown.	Bentonite Seal (7'-9')
14								
16								
18								
20							Increase in moisture.	
22								
24								
26								
28								
30							Boring terminated at 25'. Ground water was encountered at approximately 19'. Static ground water was measured at 16.13' on July 20, 2000.	2" PVC Screen - 0.010" slots (10'-25')



PENTACORE RESOURCES, LLC
 6763 W. Charleston Blvd.
 Las Vegas, Nevada 89146