WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 80608
Permit No.
Basin 212

NOTICE OF INTENT NO. 21362

1. OWNER Miller Brooks Environmental
MAILING ADDRESS 202 East Earl Drive, Suite 470
Phoenix, AZ 85012

ADDRESS AT WELL LOCATION 4710 W Charleston Blvd,
Las Vegas, NV

2. LOCATION SW 1/4 SW 1/4 Sec. 31 T 20S N/S R 61E E Clark County
PERMIT NO. (Issued by Water Resources) | Parcel No. 139-31-410-126 | Subdivision Name MW-4

3. **WORK PERFORMED**
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. **PROPOSED USE**
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. **WELL TYPE**
[ ] Cable [ ] Rotary [ ] RVC
[ ] Air [X] Other Auger

6. **LITHOLOGIC LOG**

Material	Water Strata	From	To	Thickness
Sandy SILT with Gravel		0	12	12
Sandy SILT with		12		
Caliche and Gravel			14	2
Sandy SILT with Gravel		14	16	2
Sandy SILT with		16		
Caliche and Gravel			18	2
Sandy SILT with Gravel		18	20	2
Sandy SILT with		20		
Caliche and Gravel			21	1
Silty clayey SAND		21	32	11
Sandy SILT with		32		
Caliche and Gravel			35	3
Silty clayey SAND		35	40	5

Date started 7/11/2000, 19__
Date completed 7/11/2000, 19__

7. **WELL TEST DATA**
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. **WELL CONSTRUCTION**
Depth Drilled 40 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8	Inches	0	Feet	40	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5	1.9	0.237	0	40

Perforations:
Type perforation factory slot PVC
Size perforation 0.010 inch
From 10 feet to 40 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 0-5, 5-8 bentonite
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 8 feet to 40 feet

9. **WATER LEVEL**
Static water level 19 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. **DRILLER'S CERTIFICATION**
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Tom High c/o Converse Consultants
Contractor
Address 731 Pilot Road, Suite H
Contractor
Las Vegas, NV 89119

Nevada contractor's license number issued by the State Contractor's Board 48947

Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1869

Signed
By driller performing actual drilling on-site or contractor

Date 8/1/2000

USE ADDITIONAL SHEETS IF NECESSARY