WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 81037
Permit No.
Basin 117

NOTICE OF INTENT NO. 27331

1. OWNER Kim Stewart
MAILING ADDRESS P.O Box 234 Smith NV 89430
ADDRESS AT WELL LOCATION 161 Day Lane Smith NV 89430 Lot #309 well #30 State engineer map

2. LOCATION NE ¼ NE ¼ Sec. 18 T. 11 N/S R. 24 E Lyon County
PERMIT NO. 12156 Issued by Water Resources | 10-431-13 Parcel No. | well #1 Application map Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE Propagation Fish
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☒ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other MUD

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Drilled 3-6¼" Holes around 7⅞				
Casing To Loosen From 0' To 105'				
Top Soil-Clayish		0	2	2
Coarse Sand		2	5	3
Coarse Sand-Gravel		5	32	27
Brown clay-Sand		32	35	3
Brown clay		35	60	25
Fine Sand		60	87	27
Sand-Brown clay		87	92	5
Coarse Sand-Gravel		92	105	13
Casing Moves Freely Pulled 41'6" of				
7⅞" casing				
5½" Casing won't Pull				
washed out inside 5½" To 105'				
Cut Slot in 5½" 103' To 3'6"				
Pumped 24 Bags Abentonite				
From 105' To 50' + To Fill Holes				
Filled all 3 Holes and 5½" pipe				
Let Set 1 HR				
Washed out 5½" From 50'				
Pumped Neat Cement 50' To				
Surface approx 1½ yards				

Date started 8-2 30.00
Date completed 8-9 28.00

7. OLD WELL ~~TEST~~ DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Static	2'		
5½" Casing	open To 75'		
5½" Casing	Starts 4'6"		
Below	7⅞" Casing - 3'6" Below		
Ground			

8. WELL CONSTRUCTION
Depth Drilled 103 Feet Depth Cased 103 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
7¼	Inches	0	Feet	41'6"	Feet
5½	Inches	41'6"	Feet	103	Feet
6¼	Inches	0	Feet	105	Feet 3-Sides

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
7⅞	12	5/16	+1	40'6"
5½	8	5/16	-3'6"	103
	7⅞ casing Pulled			

Perforations:
Type perforation Knife-Slots 4 Rows
Size perforation ¼" x 1½" To 2" 1 To 2 per FT
From 3'6" feet to 103' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 105
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement To 50' ☐ Cement Grout ☐ Concrete Grout
Bentonite 15-4% 9.2 LB 50' To 105'
Gravel Packed: ☐ Yes ☒ No
From — feet to — feet

9. WATER LEVEL
Static water level Start 2 feet below land surface
Artesian flow — G.P.M. — P.S.I.
Water temperature — °F Quality Old well Fair

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Ogden Drilling / DBA Contractor
Address 152 N. By Bee Ln Contractor
Yerington NV 89447
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 634
Signed [signature] By driller performing actual drilling on site or contractor
Date 8-14-00

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627