MW-3

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 81057
Permit No.
Basin 105

NOTICE OF INTENT NO. 44104

1. OWNER PARK CATTLE COMPANY, INC
MAILING ADDRESS 1300 BRICKYE RD
MINDEN, NV 89423

ADDRESS AT WELL LOCATION Mueller Lane
DOUGLAS COUNTY.

2. LOCATION SW ¼ SW ¼ Sec. 14 T. 13 N/S R. 19 E. DOUGLAS County
PERMIT NO. N/A Issued by Water Resources | 17-190-61 Parcel No. | N/A Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
DARK BROWN SILTY SAND (SM) MOIST, LOOSE		0.0	1.0	1.0
BROWN CLAYEY SAND (SC) MEDIUM DENSE MOIST.		1.0	3.0	2.0
BROWN BLACK CLAY (CH) STIFF MOIST		3.0	11.0	8.0
WATER LEVEL (STATIC)	4.0			
WATER LEVEL 1ST ENCOUNTED	11.0			
BROWN SAND (SP) MEDIUM DENSE SATURATED.		11.0	19.0	8.0

Date started MAY 30TH, 2000 ,19
Date completed MAY 30TH, 2000 ,19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 19.0 Feet Depth Cased 18.5 Feet

HOLE DIAMETER (BIT SIZE)
7 3/4 Inches From 0.0 Feet To 19.0 Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.70/ft	0.308	0.0	3.5

Perforations:
Type perforation SLOTTED
Size perforation 0.020
From 3.5 feet to 18.5 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0.0 - 1.0
Placement Method: ☐ Pumped ☐ Poured
Bentonite (1.0 - 3.5)
Sand #8
~~Gravel~~ Packed: ☒ Yes ☐ No
From 3.5 feet to 19.0 feet

Seal Type:
☐ Neat Cement
☐ Cement Grout
☒ Concrete Grout

9. WATER LEVEL
Static water level 4.5 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 62 °F Quality Silty, cloudy

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name DALE LEHMAN w/ PEZONELLA ASSOC. Contractor
Address 520 EDISON WAY Contractor
RENO, NV 89502
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1976
Signed Dale Lehman
By driller performing actual drilling on site or contractor
Date 5/31/00

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627