

Log No. 81204
 Permit No. 92A
 Basin.....

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 43878

1. OWNER JIM & THEISA KRETSCHMER ADDRESS AT WELL LOCATION.....
 MAILING ADDRESS c/o J&L Builders 10900 Red Rock Rd. (295-1320 American Flat Road Antelope Valley U.P.)
Reno, Nevada 89506 Reno, Nevada 89506
 2. LOCATION NW 1/4 NE 1/4 Sec. 33 T. 22N N/S R. 19 E Washoe County
 PERMIT NO. 079-420-11 (Antelope Valley) #5602
 Issued by Water Resources Parcel No. Red Rock Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other.....
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other.....

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Cemented decomposed granite sands		1	10	9
Brown sandy clay		10	21	11
Brown clay w/decomposed granite sands		21	33	12
Soft zone (NO WATER)		33	36	3
Brown clay w/decomposed granite sands		36	59	23
Soft zone (NO WATER)		59	61	2
Brown clay w/decomposed granite sands		61	105	44
Weathered granite with clay streaks		105	138	33
Weathered harder granite		138	218	80
Gray granite w/weathered streaks		218	321	103
Soft fracture granite (NO WATER)		321	337	16
Gray hard granite		337	347	10
Fracture (app 2 GPM)	X	347	351	4
Gray granite		351	377	26
Broken fracture, granite	X	377	383	6
Gray granite		383	400	7

8. WELL CONSTRUCTION
 Depth Drilled 400 Feet Depth Cased 400 Feet
 HOLE DIAMETER (BIT SIZE)
 From To
10 Inches 0 Feet 50 Feet
8 5/8 Inches 50 Feet 400 Feet
 Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	400

Perforations:
 Type perforation factory sawed slot
 Size perforation 3/32 x 3 x 5 around
 From 355 feet to 395 feet
 From feet to feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 50 feet Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Gravel Packed: Yes No
 From 50 feet to 400 feet

9. WATER LEVEL
 Static water level 320 feet below land surface
 Artesian flow..... G.P.M. 25 P.S.I.
 Water temperature cold °F Quality clear

Date started August 1, 2000 XX
 Date completed August 4, 2000 XX

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>25</u>		

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC.
 Address P.O. BOX 12370
RENO, NEVADA 89510
 Nevada contractor's license number 0022549
 issued by the State Contractor's Board.....
 Nevada driller's license number 923
 issued by the Division of Water Resources, the on-site driller.....
 Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date August 4, 2000