WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

**PRINT OR TYPE ONLY**
**DO NOT WRITE ON BACK**

STATE OF NEVADA
# DIVISION OF WATER RESOURCES
# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 81228
Permit No.
Basin 212

NOTICE OF INTENT NO. 20252

1. OWNER Broadbent & Associates
MAILING ADDRESS 8 West Pacific Avenue
Henderson, NV 89015

ADDRESS AT WELL LOCATION Rebel #8, 3225 North Las Vegas Boulevard, Las Vegas, NV

2. LOCATION SE 1/4 SW 1/4 Sec. 7 T 20S N/S R 62E E Clark County
PERMIT NO. MO2667 (Issued by Water Resources) | 140-07-408-003 (Parcel No.) | RMW-23 (Subdivision Name)

3. **WORK PERFORMED**
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. **PROPOSED USE**
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. **WELL TYPE**
[ ] Cable [ ] Rotary [ ] RVC
[ ] Air [X] Other Auger

6. **LITHOLOGIC LOG**

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Fill | | 0 | 3 | 3 |
| Light to medium | | 3 | | |
| colored Silty CLAY, | | | | |
| some Sand (ML) | | | 12 | 9 |
| Silty SAND with some | | 12 | | |
| Clay and little Gravel | | | | |
| (SM) | | | 18 | 6 |
| Tan Silty CLAY, some | | 18 | | |
| fine to medium Sand, | | | | |
| trace fine Gravel (ML) | | | 32 | 14 |
| Light Brown Silty | | 32 | | |
| CLAY, trace Sand (CL) | | | 49 | 17 |
| Brown Silty Clay, | | 49 | | |
| trace Sand (ML) | | | 65 | 16 |

Date started 6/1/2000 , 19__
Date completed 6/1/2000 , 19__

7. **WELL TEST DATA**
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| | | |

8. **WELL CONSTRUCTION**
Depth Drilled 65 Feet Depth Cased 65 Feet

**HOLE DIAMETER (BIT SIZE)**

| | | From | | To | |
|---|---|---|---|---|---|
| 8 | Inches | 0 | Feet | 65 | Feet |
| | Inches | | Feet | | Feet |
| | Inches | | Feet | | Feet |

**CASING SCHEDULE**

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 4.5 | 1.9 | 0.237 | 0 | 65 |
| | | | | |
| | | | | |

**Perforations:**
Type perforation Factory slot PVC
Size perforation 0.020 inch
From 20 feet to 65 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 0-15',15'-18' benton
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 18 feet to 65 feet

9. **WATER LEVEL**
Static water level 47.55 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. **DRILLER'S CERTIFICATION**
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Tom High c/o Converse Consultants (Contractor)
Address 731 Pilot Road, Suite H (Contractor)
Las Vegas, NV 89119
Nevada contractor's license number issued by the State Contractor's Board 48947
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1869
Signed (By driller performing actual drilling on-site or contractor)
Date 6/26/2000

USE ADDITIONAL SHEETS IF NECESSARY