WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 81302
Permit No.
Basin 61

NOTICE OF INTENT NO. 43616

1. OWNER Barrick Goldstrike Mines PPW-70
MAILING ADDRESS P.O. Box 29
Elko, NV 89803

ADDRESS AT WELL LOCATION Barrick Goldstrike
Minesite, North of Carlin, NV.

2. LOCATION NE 1/4 SE 1/4 Sec. 19 T 36N N/S R 50E E Eureka County
PERMIT NO. 58355 Issued by Water Resources
N/A Parcel No.
N/A Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial (Mining) ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Note: The top 88' of the well has been mined off. All of the construction details listed take this into account. A 10' piece of blank casing was welded to the remaining casing, and was cemented in place. All fill material (from 260' to T.D.) was removed prior to abandonment. Abandoned by pumping Super Plug from T.D. to 150'; Hole Plug was placed from 150' to 10'. Well capped with 10' of neat cement. Quantities Used: Super Plug = 590 cu. ft. Hole Plug = 49 cu. ft. Cement = 6 cu. ft.				

Date started 5/18/2000, 19__
Date completed 5/21/2000, 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 677 Feet Depth Cased 662 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
60	Inches	0	Feet	10	Feet
12.25	Inches	10	Feet	677	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8.625	22.36	0.250	0	662

Perforations:
Type perforation Roscoe Moss Ful Flo Louver
Size perforation 0.125"
From 10 feet to 662 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 10'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 10 feet to 677 feet

9. WATER LEVEL
Static water level 390 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature N/A °F Quality N/A

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling (Contractor)
Address P.O. Box 5279 (Contractor)
Elko, NV 89802-5279
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1410
Signed John Vierguts (By driller performing actual drilling on-site or contractor)
Date 5/23/00

USE ADDITIONAL SHEETS IF NECESSARY

BST-C