WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 81318
Permit No.
Basin 61

NOTICE OF INTENT NO. 43238

1. OWNER Barrick Goldstrike Mines PPW-21
MAILING ADDRESS P.O. Box 29
Elko, NV 89803

ADDRESS AT WELL LOCATION Barrick Goldstrike minesite, north of Carlin, NV.

2. LOCATION SE 1/4 NW 1/4 Sec. 30 T 36N N/S R 50E E Eureka County
PERMIT NO. 55150 Issued by Water Resources | NA Parcel No. | NA Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic MINING ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Note: Upper 260' of this well has been mined off. 56' below current ground level the well is off-set.				
Per discussion with DWR, we did not perforate below the sheared level. Construction data reflect the original construction.				
Prior to abandoning upper 56' of the casing was perforated. Five passes with the perforator.				
Abandoned by pumping abantonite from T.D., via tremmie. Poured hole plug to 25', and capped with neat cement.				
Quantities Used: Cement: 31 cu.ft. Hole plug: 53 cu.ft. Abantonite: 476 cu.ft.				

Date started 8/13/2000, 19__
Date completed 8/14/2000, 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1000 Feet Depth Cased 920 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
12	33.38	0.250	0	83
10	28.04	0.250	0	122
8	22.36	0.250	+2	920

Perforations:
Type perforation Louver
Size perforation 0.125" X 3"
From 620 feet to 920 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 83'
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 578 feet below land surface
Artesian flow NA G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling (Contractor)
Address P.O. Box 5279 (Contractor)
Elko, NV 89802-5279
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1410
Signed John Vierguts (By driller performing actual drilling on-site or contractor)
Date 8/24/00

USE ADDITIONAL SHEETS IF NECESSARY

B.ST-L