

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
 Log No. 71323
 Permit No. _____
 Basin 61
 NOTICE OF INTENT NO. 43624

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Duzl Completion

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1. OWNER **Barrick Goldstrike Mines PZ00-1** ADDRESS AT WELL LOCATION **Barrick Goldstrike Minesite, North of Carlin, NV**
 MAILING ADDRESS **P.O. Box 29**
Elko, NV 89803

2. LOCATION SW 1/4 SE 1/4 Sec. 19 T 36N N/S R 50E E Eureka County
 PERMIT NO. N/A Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Green grey rock with calcite		0	40	40
Brown red rock		40	60	20
Green grey rock with brown		60	100	40
Fractured black rock		100	120	20
Light green rock with calcite		120	240	120
Grey rock		240	280	40
Light green rock with calcite		280	340	60
Black rock with calcite		340	360	20
Green grey rock		360	400	40
Construction Detail:				
Cement		0	50	50
Hole Plug		50	210	160
Gravel Pack		210	250	40
Hole Plug		250	260	10
Cement		260	265	5
Hole Plug		265	290	25
Gravel		290	330	40
Hole Plug		330	400	70

8. WELL CONSTRUCTION
 Depth Drilled 400 Feet Depth Cased 320 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	To	Feet
<u>14.75</u>	<u>0</u>	<u>20</u>	Feet
<u>8.25</u>	<u>20</u>	<u>400</u>	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>10.75</u>	<u>28.04</u>	<u>0.250</u>	<u>+2</u>	<u>20</u>
<u>1: 2.375</u>	<u>5.02</u>	<u>0.218</u>	<u>+1</u>	<u>320</u>
<u>2: 2.375</u>	<u>5.02</u>	<u>0.218</u>	<u>+1</u>	<u>240</u>

Perforations:
 Type perforation Slot
 Size perforation 0.125"

From	To	feet to	feet to
<u>220'</u>	<u>240'</u>		
<u>320'</u>	<u>360'</u>		

Surface Seal: Yes No Seal Type: Neat Cement
 Depth of Seal 50' Cement Grout
 Placement Method: Pumped Concrete Grout
 Poured

Gravel Packed: Yes No
 From 1: 290 2: 210 feet to 1: 300 2: 250 feet

Date started 7/6/2000, 19
 Date completed 7/10/2000, 19

9. WATER LEVEL
 Static water level 1: 218 2: Dry feet below land surface
 Artesian flow N/A G.P.M. N/A P.S.I.
 Water temperature N/A °F Quality N/A

7. WELL TEST DATA

TEST METHOD:	Bailer	Pump	Air Lift
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
G.P.M.	Draw Down (Feet Below Static)	Time (Hours)	
<u>20</u>	<u>127'</u>	<u>1 Hour</u>	

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor
 Address P.O. Box 5279 Contractor
Elko, NV 89802-5279
 Nevada contractor's license number issued by the State Contractor's Board 0021976
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2047

Signed Michael Vanacker
 By driller performing actual drilling on-site or contractor
 Date 7/17/2000

B.S.L.