

WHITE-DIVISION OF WATER RESOURCES
CANARY-CLIENT'S COPY
PINK-WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

OFFICE USE ONLY

Log No. 81334

Permit No. 01

Basin 01

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Drill Completion

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 43625

1. OWNER BARRICK GOLDSTRIKE MINES ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE MINESITE, NORTH OF CARLIN, NV.
 MAILING ADDRESS P.O. BOX 29
ELKO, NV 89803

2. LOCATION SE 1/4 SW 1/4 Sec. 19 T. 36 N. S. R. 50 E. EUREKA County
 PERMIT NO. N/A Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thick-ness |
|--------------------|--------------|------|-----|------------|
| GREYISH GREEN ROCK | | 0 | 60 | 60 |
| GREYISH GREEN ROCK | | 60 | | |
| WITH BLACK | | | 100 | 40 |
| GREYISH GREEN ROCK | | 100 | | |
| WITH CALCITE | | | 160 | 60 |
| BLACK & GREEN ROCK | | 160 | | |
| WITH CALCITE | | | 220 | 60 |
| BLACK & GREEN ROCK | | 220 | | |
| WITH GREY CLAY | | | 260 | 40 |
| BLACK & GREEN ROCK | | 260 | | |
| WITH CALCITE | | | 300 | 40 |
| GREY & GREEN ROCK | | 300 | | |
| WITH CALCITE | | | 400 | 100 |

8. WELL CONSTRUCTION
 Depth Drilled 400 Feet Depth Cased 335 Feet

HOLE DIAMETER (BIT SIZE)
 From To
14.75 Inches 0 Feet 20 Feet
8.25 Inches 20 Feet 400 Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 10.75 | 28.04 | 0.250 | +2 | 20 |
| 1:2.375 | 5.02 | 0.218 | +1 | 260 |
| 2:2.375 | 5.02 | 0.218 | +1 | 335 |

Perforations: SLOT
 Type perforation _____
 Size perforation 0.125"
 From 220 feet to 260 feet
 From 315 feet to 335 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

CONSTRUCTION DETAIL:

| | From | To | Thick-ness |
|-----------|------|-----|------------|
| CEMENT | 0 | 50 | 50 |
| HOLE PLUG | 50 | 210 | 160 |
| GRAVEL | 210 | 269 | 59 |
| HOLE PLUG | 269 | 302 | 33 |
| GRAVEL | 302 | 346 | 44 |
| HOLE PLUG | 346 | 400 | 54 |

Surface Seal: Yes No Seal Type:
 Depth of Seal 50' Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout

Gravel Packed: Yes No
 From 1: 302 2: 210 feet to 1: 346 2: 269 feet

Date started JULY 10, 2000
 Date completed JULY 14, 2000

9. WATER LEVEL
 Static water level BOTH TUBES DRY feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature _____ °F Quality _____

7. WELL TEST DATA

| TEST METHOD: | TEST METHOD: | |
|-----------------------------------|-------------------------------|--------------|
| | G.P.M. | Time (Hours) |
| <input type="checkbox"/> Bailer | Draw Down (Feet Below Static) | |
| <input type="checkbox"/> Pump | | |
| <input type="checkbox"/> Air Lift | | |

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name LANG EXPLORATORY DRILLING
 Contractor
 Address P.O. BOX 5279
 Contractor
ELKO, NV 89802-5279
 Nevada contractor's license number 0021976
 issued by the State Contractor's Board
 Nevada driller's license number issued by the 2130
 Division of Water Resources, the on-site driller
 Signed Scott Belliston
 By driller performing actual drilling on site or contractor
 Date 7/18/2000

B.S.L.