WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 81983
Permit No.
Basin 212

NOTICE OF INTENT NO. 21772

1. OWNER Dalby Shirley
MAILING ADDRESS 2012 Western LV Nev. 89102

ADDRESS AT WELL LOCATION Vacant El Campo Grande & Rebecca

2. LOCATION SE ¼ ~~NE~~ SW ¼ Sec. 26 T. 19S N/S R. 60 E. Clark County
PERMIT NO. (Issued by Water Resources) | Parcel No. 125-26-403-004 | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Popcorn Caliche | | 0 | 3 | |
| Caliche | | 3 | 8 | |
| Popcorn Caliche | | 8 | 90 | |
| Caliche | | 90 | 120 | |
| Clay | | 120 | 280 | |
| Clay & Water | xx | 280 | 320 | |
| Caliche | | 320 | 360 | |
| Caliche & Water | xx | 360 | 420 | |

Date started 11/17/00, 19
Date completed 11/22/00, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| | | |

8. WELL CONSTRUCTION
Depth Drilled 420 Feet Depth Cased 420 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 12 1/4 Inches | 0 Feet | 55 Feet |
| 7 7/8 Inches | 55 Feet | 420 Feet |
| Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 8 5/8 | 16.94 | .188 | +1 | 55 |
| 5 1/2 | SRD 21 | PVC | 0 | 420 |

Perforations:
Type perforation Factory
Size perforation 1/8 x Sieve type
From 350 feet to 370 feet
From 390 feet to 410 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 55
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 189 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name ~~xxxxxx~~ Vernon H. Dimick (Contractor)
Address 5360 Bonita Vista (Contractor)
Las Vegas, Nev. 89149
Nevada contractor's license number issued by the State Contractor's Board 10062
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 552
Signed V. H. Dimick (By driller performing actual drilling on site or contractor)
Date 12-15-00

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627