


STATE OF NEVADA  
 DIVISION OF WATER RESOURCES

OFFICE USE ONLY  
 Log No. 82246  
 Permit No. \_\_\_\_\_  
 Basin 6  


WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 38325

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

1. OWNER Barrick Goldstrike Mines - VD98-5 ADDRESS AT WELL LOCATION Barrick Goldstrike  
 MAILING ADDRESS P.O. Box 29 Minesite, North of Carlin, NV.  
Elko, NV 89803

2. LOCATION NE 1/4 SW 1/4 Sec. 19 T 36N N/S R 50 E Eureka County  
 PERMIT NO. 55140 Parcel No. N/A Subdivision Name N/A  
Issued by Water Resources

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
<b>Abandoned per procedure discussed with DWR.</b>				
<b>Abandoned by pumping abantonite via tremmie to 346', then poured hole plug to 50', and capped with neat cement.</b>				
<b>Quantities Used:</b>				
<b>Cement: 18 cu.ft.</b>		<b>0</b>	<b>50</b>	<b>50</b>
<b>Hole Plug: 55 cu.ft.</b>		<b>50</b>	<b>346</b>	<b>296</b>
<b>Abantonite: 71 cu.ft.</b>		<b>346</b>	<b>640</b>	<b>294</b>

*Handwritten notes in left margin:*  
 11/23/2000  
 7 PM 12:18  
 STATE ENGINEER'S OFFICE

8. WELL CONSTRUCTION  
 Depth Drilled 650 Feet Depth Cased 640 Feet

HOLE DIAMETER (BIT SIZE)

From		To	
<u>17.50</u> Inches	<u>0</u> Feet	<u>19</u> Feet	
<u>12.25</u> Inches	<u>19</u> Feet	<u>650</u> Feet	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>14</u>	<u>36.71</u>	<u>0.250</u>	<u>0</u>	<u>19</u>
<u>6.625</u>	<u>17.02</u>	<u>0.250</u>	<u>+2</u>	<u>640</u>

Perforations:  
 Type perforation Louver  
 Size perforation 0.125"

From	To
<u>60</u> feet	<u>640</u> feet
_____ feet	_____ feet
_____ feet	_____ feet
_____ feet	_____ feet
_____ feet	_____ feet

Surface Seal:  Yes  No  
 Depth of Seal 50'  
 Placement Method:  Pumped  Poured  
 Seal Type:  Neat Cement  Cement Grout  Concrete Grout

Gravel Packed:  Yes  No  
 From 50 feet to 650 feet

9. WATER LEVEL  
 Static water level 346.58 feet below land surface  
 Artesian flow N/A G.P.M. \_\_\_\_\_ P.S.I. \_\_\_\_\_  
 Water temperature Warm °F Quality Fair

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor  
 Address P.O. Box 5279 Contractor  
Elko, NV 89802-5279  
 Nevada contractor's license number issued by the State Contractor's Board 0021976  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2143

Signed Brant Bowen  
 By driller performing actual drilling on-site or contractor  
 Date 12/5/00

Date started 11/23/2000, 19  
 Date completed 11/23/2000, 19

7. WELL TEST DATA

TEST METHOD:	Draw Down (Feet Below Static)		Time (Hours)
	G.P.M.		
<input type="checkbox"/> Bailer			
<input type="checkbox"/> Pump			
<input type="checkbox"/> Air Lift			

*Handwritten initials:* B.S.L.