WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 82248
Permit No.
Basin 61

NOTICE OF INTENT NO. 43248

1. OWNER Barrick Goldstrike Mines EW-5
MAILING ADDRESS P.O. Box 29
Elko, NV 89803

ADDRESS AT WELL LOCATION Barrick Goldstrike minesite, north of Carlin, NV.

2. LOCATION SW 1/4 NE 1/4 Sec. 19 T 36N N/S R 50E E Eureka County
PERMIT NO. 55141 Issued by Water Resources | NA Parcel No. | NA Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Note: The top 200' of this well have been mined off. The construction data reflect the original construction. This well will be beneath the anticipated pit lake.				
Abandoned by pumping abantonite via tremmie from T.D. to 133', hole plug to 4', and capped with neat cement.				
Quantities Used:				
Cement: 3 cu.ft.		0	4	4
Hole plug: 101 cu.ft.		4	133	129
Abantonite: 336 cu.ft.		133	290	157

Date started 8/17/2000, 19__
Date completed 8/18/2000, 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 490 Feet Depth Cased 480 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
36	Inches	0	Feet	40	Feet
17.5	Inches	40	Feet	490	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
20	78.60	0.375	0	40
12	33.38	0.250	0	480

Perforations:
Type perforation Louver
Size perforation 0.250"
From 120 feet to 480 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 100'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 100 feet to 490 feet

9. WATER LEVEL
Static water level 215 feet below land surface
Artesian flow NA G.P.M. NA P.S.I.
Water temperature NA °F Quality NA

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling (Contractor)
Address P.O. Box 5279 (Contractor)
Elko, NV 89802-5279
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1888
Signed David Doriot (By driller performing actual drilling on-site or contractor)
Date 8/29/2000

USE ADDITIONAL SHEETS IF NECESSARY

BSTL