WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 82425
Permit No. 65948 70257
Basin 212

NOTICE OF INTENT NO. 48926

1. OWNER Moapa Band of Paiutes
MAILING ADDRESS PO Box 340
Moapa, NV 89025

ADDRESS AT WELL LOCATION
ECP-1

2. LOCATION SE ¼ NE ¼ Sec. 15 T 16 X N/S R 64 E Clark County
PERMIT NO. 65948,W2092 (Issued by Water Resources) 067-00-001-017 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE Power
☐ Domestic ☐ Irrigation ☒ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
see attached sheet				

RECEIVED 01 MAY 11 AM 6:26 DCNR/DWR LAS VEGAS OFFICE

DCNR/DWR Received 2001 LAS VEGAS OFFICE

Date started 3/14/00, 19
Date completed 7/16/00, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1170 Feet Depth Cased 1125 Feet

HOLE DIAMETER (BIT SIZE)
see attached sheet
Inches From Feet To Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
see attached sheet				

Perforations: see attached sheet
Type perforation
Size perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 62
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 414 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Thompson Drilling Co., Inc. (Contractor)
Address 7227 Hauck Street (Contractor)
Las Vegas, NV 89118
Nevada contractor's license number 4286A issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2074
Signed Richard K. Thompson (By driller performing actual drilling on site or contractor)
Date 3/23/01

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

Log ~~[illegible]~~ 82425

Owner: Moapa Band of Paiutes ECP-1
Notice of Intent: 18926

LITHOLOGIC LOG

MATERIAL	FROM	TO	THICK
calcrete	0	19	19
mudstone	19	158	139
linestone, sandstone,clay	158	167	9
mudstone	167	211	44
limestone	211	360	149
limestone & sandstone	360	400	40
limestone	400	410	10
limestone & sandstone	410	415	5
sandstone	415	435	20
limestone & sandstone	435	470	35
limestone	470	550	80
limestone & siltstone	550	580	30
limestone & sandstone	580	600	20
limestone	600	640	40
limestone & dolomite	640	670	30
limestone	670	745	75
siltstone & limestone	745	765	20
sandstone, limestone	765	790	25
limestone,sand & siltstone	790	860	70
limestone	860	905	45
siltstone & limestone	905	920	15
limestone	920	995	75
sandstone	995	1010	15
limestone	1010	1030	20
limestone,sand & siltstone	1030	1050	20
limestone	1050	1150	100
dolomite & sandstone	1150	1170	20
			0
			0
			0
			0
			0
			0
			0
			0
			0
			0
			0
TOTAL			1170

HOLE DIAMETER (BIT SIZE)

INCHES	FROM	TO
26	0	8
24 1/4	8	213.5
17	213.5	701
6 5/8	1055	1170

CASING/SCREEN SCHEDULE

SIZE (OD)	WALL (IN)	TO	FROM
26		0	3
18	0.3125	0	600
14	0.3125	600	701
10 3/4	0.25	701	1051
6 5/8	0.25	1051	1125

PERFORATIONS

TYPE: mill slots
SIZE: 1/8

OD	FROM	TO
14	600	701
10 3/4	701	1051
6 5/8	1051	1125

DCNR/DWR
Received
2001
LAS VEGAS OFFICE