WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 82426
Permit No. 65949
Basin 218
70259

NOTICE OF INTENT NO. 18927

1. OWNER Moapa Band of Paiutes
MAILING ADDRESS PO Box 340
Moapa, NV 89025

ADDRESS AT WELL LOCATION
ECP-2

2. LOCATION NE ¼ NE ¼ Sec. 15 T 16 ☒S R 64 E Clark County
PERMIT NO. 65949, W2095 (Issued by Water Resources) | 067-00-001-017 (Parcel No.) | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE Power
☐ Domestic ☐ Irrigation ☒ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
see attached sheet				

Date started 4/18/00, 19
Date completed 12/6/00, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1228 Feet Depth Cased 139 Feet

HOLE DIAMETER (BIT SIZE)
see attached sheet
Inches Feet To Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
see attached sheet				

Perforations:
Type perforation n/a
Size perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 55
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 416 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Thompson Drilling Co., Inc. (Contractor)
Address 7227 Hauck Street (Contractor)
Las Vegas, NV 89118
Nevada contractor's license number issued by the State Contractor's Board 4286A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2074
Signed Richard K. Thompson (By driller performing actual drilling on site or contractor)
Date 3/23/01

RECEIVED 01 MAR 26 AM 9:28 STATE ENGINEER'S OFFICE

DCNR/DWR Received 2001 LAS VEGAS OFFICE

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

Log # 82426

Owner: Moapa Band of Paiutes ECP-2
Notice of Intent: 18927

LITHOLOGIC LOG

MATERIAL	FROM	TO	THICK
calcrete	0	10	10
mudstone	10	95	85
limestone & mudstone	95	118	23
limestone & sandstone	118	230	112
limestone	230	350	120
limestone & mudstone	350	380	30
limestone & sandstone	380	420	40
limestone	420	480	60
limestone & sandstone	480	500	20
lime,sand & mud stone	500	600	100
sandstone, limestone	600	620	20
limestone, sandstone	620	680	60
sand,lime & silt stone	680	715	35
limestone	715	795	80
sandstone, limestone	795	815	20
limestone	815	860	45
siltstone, limestone	860	875	15
dolomite	875	905	30
limestone & dolomite	905	930	25
limestone	930	980	50
lime,sand & silt stone	980	1000	20
limestone	1000	1145	145
sand, silt & lime stone	1145	1205	60
sandstone, dolomite	1205	1215	10
limestone & dolomite	1215	1228	13
			0
			0
			0
			0
			0
			0
			0
			0
			0
			0
			0
			0
			0
TOTAL			1228

HOLE DIAMETER (BIT SIZE)

INCHES	FROM	TO
24	0	140
12	140	515
8.5	515	695
7 7/8	695	1228

CASING/SCREEN SCHEDULE

SIZE (OD)	WALL (IN)	TO	FROM
18	0.3125	+.5	139

DCNR/DWR
Received
2001
LAS VEGAS OFFICE