WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 82448
Permit No.
Basin 212

NOTICE OF INTENT NO. 20960.

1. OWNER Thatcher Chemical Co Daniel Hornus NDOT
MAILING ADDRESS 1263 S Stewart st RM 104A Carson City Nev. 89712
ADDRESS AT WELL LOCATION Southwest Pedestrain Island 215 & 95 Henderson Nevada 850 W Lake Mead Dr

2. LOCATION NE ¼ SE ¼ Sec. 14 T. 22 N/S R. 62 E. Clark County
PERMIT NO. Issued by Water Resources | Parcel No. 178.14-701.001 | Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☑ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Class two Road Material | | 0 | 10 | 10 |
| Sand Gravel Lt Brown | | 10 | 85 | 75 |
| Sand Gravel DK Brown | | 85 | 150 | 65 |

DCNR/DWR Received MAR 9 2001 LAS VEGAS OFFICE

Date started Feb 2, 2001
Date completed Feb 2, 2001

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☑ Pump ☐ Air Lift

| | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|---|
| Pumped 3 Well Bores until Water cleared up took Sample | | | |

8. WELL CONSTRUCTION
Depth Drilled 150 Feet Depth Cased 150 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 6 Inches | | 0 Feet | 150 Feet |
| Inches | | Feet | Feet |
| Inches | | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 2 | PVC | Monitoring | 0 | 150 |

Perforations:
Type perforation Mill slot
Size perforation .020 slot
From 90 feet to 150 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☑ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☑ Yes ☐ No
From 150 feet to 88 feet

9. WATER LEVEL
Static water level 46 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 78 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Layne Christensen Contractor
Address 12030 E. Riggs Rd. Contractor
Chandler AZ. 85249
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2021
Signed Michael D. Wells
By driller performing actual drilling on site or contractor
Date 3-9-2001

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627