WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 82702
Permit No.
Basin

NOTICE OF INTENT NO. 220

1. OWNER Boomtown Hotel & Casino
MAILING ADDRESS P.O. Box 399
Verdi, NV 89439

ADDRESS AT WELL LOCATION Well #11 west side of parking lot & casino

2. LOCATION SW 1/4 NW 1/4 Sec. 16 T 19N N/S R 18E E Washoe County
PERMIT NO. Waiver W-523 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [✓] Test
[X] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
clay		0	5	
clay & cobbles		5	75	70
granite & boulders		75	80	5
boulders & sand		80	310	230
loss circulation		310	340	30

Date started 9/12/00, 19__
Date completed 12/6/00, 19__

7. WELL TEST DATA

TEST METHOD: [ ] Bailer [X] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
400	138	8 hrs

8. WELL CONSTRUCTION

Depth Drilled 340 Feet Depth Cased 320 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
24 Inches	0 Feet	101 Feet
14-3/4 Inches	0 Feet	340 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10 ID		.250	0	150
10 ID		.250	220	240
10 ID		.250	310	320
16 OD conductor		5/16	0 - 101	

Perforations:
Type perforation mill slot
Size perforation .100
From 150 feet to 220 feet
From 240 feet to 310 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 101
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 0 feet to 340 feet

9. WATER LEVEL
Static water level 93.4 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, Nevada 89445
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1572
Signed [signature] (By driller performing actual drilling on-site or contractor)
Date 12/13/00