WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 83514
Permit No.
Basin 102

NOTICE OF INTENT NO. [redacted]5

1. OWNER MIKE CASEY
MAILING ADDRESS 1550 ALLEN ROAD
FALLON, NV 89406

ADDRESS AT WELL LOCATION 2530 7TH, Silver Springs

2. LOCATION NE 1/4 SW 1/4 Sec. 7 T 17 N/S R 25 E LYON County
PERMIT NO. Issued by Water Resources
17-331-16 Parcel No.
Stockton Sub Subdivision Name

3. WORK PERFORMED
[x] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[x] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[x] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
AQUAGUARD SEAL				
TOP SOIL		0	1	1
BRN SAND		1	15	14
BRN CLAY		15	18	3
BRN SAND		18	43	25
GREY CLAY		43	60	17
RED CLAY		60	70	10
RED SIKT		70	80	10
BRNB CLAY		80	85	5
MC GRAVELS/CLAY		85	170	85
GREY CLAY		170	175	5
BROWN GRAVELS	X	175	187	12

RECEIVED 00 SEP 26 AM 11:19 STATE ENGINEER'S OFFICE

Date started 8/2/2000, 19__
Date completed 9/2/2000, 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
20		1 HR

8. WELL CONSTRUCTION
Depth Drilled 187 Feet Depth Cased 187 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	50	Feet
6 5/8	Inches	50	Feet	187	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.9	.188	+2	187

Perforations:
Type perforation MACHINE SLIT
Size perforation .080
From 178 feet to 182 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [ ] Yes [X] No
From feet to feet

9. WATER LEVEL
Static water level 43 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature COOL °F Quality UNTESTED

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WELSCO CORP. Contractor
Address P. O. BOX 888 Contractor
FALLON, NV 89406
Nevada contractor's license number issued by the State Contractor's Board 11752
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1996
Signed [signature] By driller performing actual drilling on-site or contractor
Date 9/24/2000

USE ADDITIONAL SHEETS IF NECESSARY