

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
 WELL DRILLER'S REPORT

OFFICE USE ONLY
 Log No. 8381
 Permit No. 377B
 Basin 377B

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 58336

1. OWNER Round Mountain Gold Co. DW-27
 MAILING ADDRESS P.O. Box 480
Round Mountain, NV 89045

ADDRESS AT WELL LOCATION Round Mountain Gold minesite, near Round Mountain, NV.

2. LOCATION SE 1/4 SW 1/4 Sec. 19 T 10N
 PERMIT NO. 67024-T Parcel No. N/A

N/S R 44E E Nye County
 Subdivision Name N/A

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Brown and tan rock		0	190	190
Red and brown rock with trace clay		190	280	90
White clay with trace of red rock		280	290	10
Tan clay		290	300	10
White rock and clay		300	310	10
Brown and red rock, trace brown clay		310	380	70
Grey rock with trace white clay		380	490	110
White rock with trace brown clay		490	520	30
Brown clay trace of rock		520	550	30
Grey clay trace of rock		550	570	20
Brown rock trace of clay		570	600	30
Grey clay		600	620	20
Brown rock		620	680	60
Black and grey rock		680	700	20
Brown rock		700	710	10
Grey and brown rock		710	730	20
Grey and black rock		730	890	160
Brown rock		890	930	40
Grey and brown rock		930	960	30
Brown rock		960	1030	70
Black rock trace of clay		1030	1035	5

8. WELL CONSTRUCTION

Depth Drilled 1035 Feet Depth Cased 1000.89 Feet

HOLE DIAMETER (BIT SIZE)

From		To	
<u>26</u> Inches	<u>0</u> Feet	<u>50</u> Feet	
<u>17.5</u> Inches	<u>50</u> Feet	<u>1035</u> Feet	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>20</u>	<u>78.60</u>	<u>0.375</u>	<u>0</u>	<u>52</u>
<u>10.750</u>	<u>40.48</u>	<u>0.375</u>	<u>+2</u>	<u>518.91</u>

Perforations:

Type perforation Bridge slot, wire wrap, louvred
 Size perforation 0.125"

From <u>Bridge 518.95</u> feet to <u>758.52</u> feet
From <u>Wire wrap 758.52</u> feet to <u>918.67</u> feet
From <u>Louvred 918.67</u> feet to <u>998.89</u> feet
From _____ feet to _____ feet
From _____ feet to _____ feet

Surface Seal: Yes No Seal Type: Neat Cement
 Depth of Seal 50' Cement Grout
 Placement Method: Pumped Poured Concrete Grout
 Gravel Packed: Yes No
 From 20 feet to 1035 feet

Date started 2/19/2001, 19
 Date completed 2/27/2001, 19

7. WELL TEST DATA

TEST METHOD:	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift G.P.M. <u>320</u>	<u>130</u>	<u>15 Minutes</u>

9. WATER LEVEL

Static water level 345 feet below land surface
 Artesian flow N/A G.P.M. N/A P.S.I.
 Water temperature Warm °F Quality Good

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Lang Exploratory Drilling Contractor
 Address P.O. Box 5279 Contractor
Elko, NV 89802-5279
 Nevada contractor's license number issued by the State Contractor's Board 0021976
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2144
 Signed Paul Stoddard
 By driller performing actual drilling on-site or contractor
 Date 3/10/2001

B.S.L.