WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 83856
Permit No. 87
Basin

NOTICE OF INTENT NO. 45299

1. OWNER Washoe County Dept Water Resources
MAILING ADDRESS 4930 Energy way Reno NV 89502
ADDRESS AT WELL LOCATION Infront of 1665 Lisbon Ave

2. LOCATION SW ¼ SE ¼ Sec 13 T 19 N/S R 19 E Washoe County
PERMIT NO. (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☑ Other Sonic

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Tan Sandy silt Dry		0	10.5	10.5
Dry Sandy silt turning light Gry		10.5	13'	2.5
Tan silty fine sandy dry		13'	16.5	3.5
Cobbles		16.5	17.5	
Gray, dry silty fine sand		17.5	26.5	9
w/ 20% coarse sand	26			
& rounded Cobbles				
olive gray silty gravel		26.5	32	5.5
cobble sand mixture				
wet				
olive gray, black organic		32	34.5	2.5
looking dense silt				
olive gray silty gravel		34.5	40	5.5
cobble sand mixture				

Date started 3/15/01, 19
Date completed 3/15/01, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 40 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
4"	Inches	Ø Feet	40 Feet
6"	Inches	Ø Feet	40 Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		Sch 40	0	20

Perforations:
Type perforation Factory
Size perforation 020
From 20' feet to 40' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal ~~26'~~ 12
Placement Method: ☑ Pumped ☐ Poured
Seal Type: ☑ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☑ Yes ☐ No
From 15 feet to 40 feet

9. WATER LEVEL
Static water level 26' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Boart Longyear (Contractor)
Address P.O. Box 1000 Dayton NV 89403 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2168
Signed (By driller performing actual drilling on site or contractor)
Date 4/9/01

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627