WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 83988
Permit No.
Basin 92A

NOTICE OF INTENT NO. 47105

1. OWNER BILLY MOONEYHAM
MAILING ADDRESS P.O. Box 921
Red Bluff, CA 96080

ADDRESS AT WELL LOCATION
10255 Pathfinder Drive
Reno, Nevada 89506

2. LOCATION NE ¼ SE ¼ Sec. 14 T. 21N N/S R. 18 E. Washoe County
PERMIT NO. (Issued by Water Resources) 087-050-01 (Parcel No.) Silver Knolls (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Brown sandy clay | | 0 | 12 | 12 |
| Granite sands | | 12 | 13 | 1 |
| Brown sandy clay | | 13 | 28 | 15 |
| Granite sands | | 28 | 32 | 4 |
| Brown sandy clay | | 32 | 115 | 83 |
| Granite sands & gravels | | 115 | 118 | 3 |
| Brown sandy clay | | 118 | 132 | 14 |
| Soft zone | | 132 | 137 | 5 |
| Brown sandy clays | | 137 | 185 | 48 |
| Soft zone, sandy clays | | 185 | 211 | 26 |
| Brown clay | | 211 | 215 | 4 |
| Soft zone, sand & gravel | X | 215 | 221 | 6 |
| Brown sandy clay | | 221 | 235 | 14 |
| Sands & gravels | X | 235 | 240 | 5 |
| Brown sandy clay | | 240 | 251 | 11 |
| Sand & gravels | X | 251 | 265 | 14 |
| Brown sandy clay | | 265 | 275 | 10 |

Date started June 27, 2001, 19
Date completed June 28, 2001, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| 25.5 | | |

8. WELL CONSTRUCTION
Depth Drilled 275 Feet Depth Cased 275 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 10 Inches | 0 Feet | 50 Feet |
| 8 5/8 Inches | 50 Feet | 275 Feet |
| Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6 5/8 | | .188 | 0 | 275 |

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 230 feet to 270 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50 feet
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 275 feet

9. WATER LEVEL
Static water level 174 feet below land surface
Artesian flow G.P.M. 25.5 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed [signature] (By driller performing actual drilling on site or contractor)
Date June 28, 2001

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627