WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 84053
Permit No. 75176
Basin 230 DB

NOTICE OF INTENT NO. 21668

1. OWNER Larry Olson
MAILING ADDRESS Cottonwood Ave Amargosa Valley, NV 89020
ADDRESS AT WELL LOCATION Cottonwood Ave Amargosa Valley, NV 89020

2. LOCATION NE ¼ NE ¼ Sec. 1 T. 17 N/S R. 48 E. NYE County
PERMIT NO. 75176 DB (Issued by Water Resources) 19-681-01 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE Commercial
☒ ~~Domestic~~ ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
DB ☐ Air ☒ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand		0	25	25
gravel w/snd.		25	35	10
White cly.		35	45	10
small gravel		45	55	10
tan cly.		55	71	16
limestone		71	75	4
cly. w/snd.		75	105	30
gravel	1st	105	113	8
limestone		113	120	7
snd.		120	143	23
tan cly.		143	158	15
limestone w/cly. layers		158	180	22
Bottom of Hole			180	

DCNR/DWR AUG 10 2001 NEVADA OFFICE

Date started 7-8-01, 19
Date completed 7-12-01, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 180 Feet Depth Cased 180 Feet

HOLE DIAMETER (BIT SIZE)
12½ Inches From 0 Feet To 180 Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	PVC		0	180
Surface Protective casing:				
7'X8"	steel	.1808		

Perforations:
Type perforation Machined
Size perforation 3" X 1/8" Every 12"
From 100 feet to 140 feet
From 160 feet to 170 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 180 feet

9. WATER LEVEL
Static water level 90 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Cook Drilling Co. (Contractor)
Address HCR 70 Box 543 (Contractor)
Amargosa Valley, Nv. 89020
Nevada contractor's license number issued by the State Contractor's Board 5376 A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2160
Signed [signature]
By driller performing actual drilling on site or contractor
Date

1