WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 84115
Permit No.
Basin 85

NOTICE OF INTENT NO. 47111

1. OWNER NOLAN LITTLE
MAILING ADDRESS 400 Yellow Pine, Reno, Nevada 89511
ADDRESS AT WELL LOCATION 470 Calle De La Plata, Sparks, Nevada 89436

2. LOCATION NW ¼ SW ¼ Sec. 19 T. 21N N/S R. 21 E. Washoe County
PERMIT NO. (Issued by Water Resources) 076-401-01 (Parcel No.) Spanish Springs (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	2	2
Sandy clays		2	12	10
Granite boulders		12	13	1
Brown sandy clay		13	35	22
Weathered granite		35	85	50
Rusty soft granite		85	90	5
Weathered granite		90	140	50
Fracture (NO WATER)		140	141	1
Weathered granite		141	180	39
Fracture granite (NO H2O)		180	182	2
Weathered granite		182	230	48
Hard white granite		230	237	7
Soft fracture granite	X	237	345	8
Weathered granite		345	379	34
Soft fracture granite	X	379	390	11
Weathered granite		390	397	7

Date started August 2, 2001, 19
Date completed August 6, 2001, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
16		

8. WELL CONSTRUCTION
Depth Drilled 397 Feet Depth Cased 397 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches	0 Feet	50 Feet	
8 5/8 Inches	50 Feet	397 Feet	
Inches	Feet	Feet	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	397

Perforations:
Type perforation factory sawed slo
Size perforation 3/32 x 3 x 5 around
From 332 feet to 352 feet
From 372 feet to 392 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50 feet
Placement Method: [ ] Pumped [X] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 397 feet

9. WATER LEVEL
Static water level 270 feet below land surface
Artesian flow G.P.M. 16 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510

Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923

Signed (By driller performing actual drilling on site or contractor)
Date August 7, 2001

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627