WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 24159
Permit No.
Basin 92B

NOTICE OF INTENT NO. 45057

1. OWNER LARRY & HEATHER PERRY
MAILING ADDRESS 11615 Fir Drive
Reno, Nevada 89506

ADDRESS AT WELL LOCATION 1355 Argonaught
Reno, Nevada 89506

2. LOCATION SE ¼ SW ¼ Sec. 26 T. 21N N/S R. 19 E. Washoe County

PERMIT NO. (Issued by Water Resources) | 079-440-35 (Parcel No.) | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Brown sandy clay		1	3	2
Brown fine sand		3	12	9
Brown sandy clay		12	55	43
Granite sands		55	58	3
Brown sandy clays		58	78	20
Weathered granite with clay streaks		78	110	32
weathered granite		110	190	80
Soft zone (aap 3 GPM)	X	190	196	6
Weathered granite		196	240	44
Soft weathered granite	X	240	245	5
Weathered granite		245	280	35
Soft zone (rusty granite)	X	280	285	5
Weathered ganite		285	300	15

Date started Juny 2, 2001, 19
Date completed July 3, 2001, 19

7. WELL TEST DATA

TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30+		

8. WELL CONSTRUCTION
Depth Drilled 300 Feet Depth Cased 300 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
8 5/8 Inches		50 Feet	300 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	300

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 234 feet to 254 feet
From 274 feet to 294 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50 feet
Placement Method: ☐ Pumped ☒ Poured

Seal Type:
☒ Neat Cement
☐ Cement Grout
☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 300 feet

9. WATER LEVEL
Static water level 143 feet below land surface
Artesian flow G.P.M. 30+ P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510

Nevada contractor's license number issued by the State Contractor's Board 0022549

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923

Signed (By driller performing actual drilling on site or contractor)
Date July 5, 2001

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627