WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 84208
Permit No.
Basin 66

NOTICE OF INTENT NO. 42193

1. OWNER Newmont Gold Co
MAILING ADDRESS P.O. Box 69
Golconda NV 89414

ADDRESS AT WELL LOCATION Twin Creeks Mine
Humboldt County

2. LOCATION NW ¼ SE ¼ Sec. 5 T. 38 N/S R. 43 E. Humboldt County
PERMIT NO. MO 9334 (Issued by Water Resources) Parcel No. 7-131-03 Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Ran trimmy to 160'				
Pumped Abantonite slurry				
to Surface				
Well # MO 384305-10				

Date started 6-25 2001
Date completed 6-25 2001

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled ____ Feet Depth Cased ____ Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:
Type perforation
Size perforation
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From ____ feet to ____ feet

9. WATER LEVEL
Static water level ____ feet below land surface
Artesian flow ____ G.P.M. ____ P.S.I.
Water temperature ____ °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Hard Rock Exploration (Contractor)
Address 1000 Barrington Ave (Contractor)
Elko NV 89801
Nevada contractor's license number issued by the State Contractor's Board 0048915
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1670
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 6-30-01

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY
M/0 384305-10
PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 49750
Permit No.
Basin

NOTICE OF INTENT NO. No Intent See Waiver

1. OWNER Eklund Drilling Santa Fe Pacific
MAILING ADDRESS P.O Box 2786
Elko Nev
ADDRESS AT WELL LOCATION Twin Creeks Mine
Humboldt Co

2. LOCATION NW ¼ SE ¼ Sec. 5 T 35 N S R 43 E Humboldt County
PERMIT NO. M/0 933 A Issued by Water Resources
Parcel No. 7-131-03
Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium		0	160	160

Date started 19
Date completed 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 160 Feet Depth Cased 160 Feet

HOLE DIAMETER (BIT SIZE)

		From		To
14 Inches	0 Feet	10 Feet		
6 3/4 Inches	10 Feet	160 Feet		
Inches	Feet	Feet		

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.5		.25	0	160

Perforations:
Type perforation Slot
Size perforation .020
From 40 feet to 160 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 10
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 12 feet to 160 feet

9. WATER LEVEL
Static water level 82 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 60 °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Co. Contractor
Address P.O. Box 2786 Contractor
Elko, Nevada 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 177
Signed Dennis L White By driller performing actual drilling on site or contractor
Date June 28 1995

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 3-91) (01-47)

384305-10D (or 10)