

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
 Log No. 84774
 Permit No. 63127
 Basin 61

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 47548

1. OWNER Barrick Goldstrike Mines PPW-100 ADDRESS AT WELL LOCATION Barrick Goldstrike minesite, north of Carlin, NV
 MAILING ADDRESS P.O. Box 29
Elko, NV 89803

2. LOCATION SW 1/4 NE 1/4 Sec. 19 T 36N N/S R 50E E Eureka County
 PERMIT NO. 63127 Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE mining
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other Flooded

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Submersible pump and motor had lodged in well while being pulled. Tagged at 305' with tremie pipe; able to drive it to bottom prior to abandoning.				
Abandoned by pumping abantonite via tremie from 900' to 100'. poured hole plug to 20', and capped with cement.				
Quantities Used:				
Neat cement: 35.4 cu.ft.				
Hole plug: 71 cu.ft.				
Abantonite: 351 cu.ft.				
Construction Detail:				
Cement		0	50	50
Hole plug		50	200	150
Gravel pack		200	910	710

Date started 10/13/2001, 19
 Date completed 10/13/2001, 19

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
 Depth Drilled 910 Feet Depth Cased 900 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	To	Feet	Feet
<u>19</u>	<u>0</u>	<u>34.58</u>		
<u>14.75</u>	<u>34.58</u>	<u>910</u>		

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>16</u>	<u>42.05</u>	<u>0.250</u>	<u>0</u>	<u>34.58</u>
<u>8.625</u>	<u>22.36</u>	<u>0.250</u>	<u>+2</u>	<u>900</u>

Perforations:
 Type perforation Louver
 Size perforation 0.125" x 2"

From	To	Feet	Feet
<u>217.03</u>	<u>900</u>		

Surface Seal: Yes No
 Depth of Seal 34.58'
 Placement Method: Pumped Poured
 Seal Type: Neat Cement Cement Grout Concrete Grout

Gravel Packed: Yes No
 From 200 feet to 910 feet

9. WATER LEVEL
 Static water level Dry feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature _____ °F Quality _____

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor
 Address P.O. Box 5279 Contractor
Elko, NV 89802-5279
 Nevada contractor's license number issued by the State Contractor's Board 0021976
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2095
 Signed Joe Crawford
 By driller performing actual drilling on-site or contractor
 Date 10/16/01

B.S.L