

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
 Log No. 84779
 Permit No. 55140
 Basin 61

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 47549

1. OWNER Barrick Goldstrike Mines PPW-102 ADDRESS AT WELL LOCATION Barrick Goldstrike minesite, north of Carlin, NV.
 MAILING ADDRESS P.O. Box 29
Elko, NV 89803

2. LOCATION NE 1/4 SW 1/4 Sec. 19 T 36N N/S R 50E E Eureka County
 PERMIT NO. 55140 Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED
 New Well Replace Recondition Deepen Abandon Other

4. PROPOSED USE mining
 Domestic Irrigation Test Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Found casing to be sheared at 58.7', and could not get video camera deeper than 68.8'. due to a bridge, consisting of gravel pack and native material. Ran in BQ tremie, and circulated air conventional to 290'.				
Abandoned by pumping abantonite via tremie from 290' to static water level, poured hole plug and abantonite to 59', and capped with neat cement.				
Quantities Used: Neat cement: 24 cu.ft Hole plug: 26 cu.ft. Abantonite: 82 cu.ft.				

Date started 10/4/2001, 19
 Date completed 10/5/2001, 19

7. WELL TEST DATA

TEST METHOD:	<input type="checkbox"/> Bailer	<input type="checkbox"/> Pump	<input type="checkbox"/> Air Lift
G.P.M.	Draw Down (Feet Below Static)	Time (Hours)	

8. WELL CONSTRUCTION

Depth Drilled 308 Feet Depth Cased 300 Feet

HOLE DIAMETER (BIT SIZE)

From		To	
<u>17</u> Inches	<u>0</u> Feet	<u>20</u> Feet	
<u>12.25</u> Inches	<u>20</u> Feet	<u>308</u> Feet	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>13.375</u>	<u>68.75</u>	<u>0.500</u>	<u>0</u>	<u>20</u>
<u>8.625</u>	<u>22.36</u>	<u>0.250</u>	<u>+2</u>	<u>300</u>

Perforations:
 Type perforation Louwer
 Size perforation 0.125"

From 20 feet to 300 feet
 From _____ feet to _____ feet

Surface Seal: Yes No
 Depth of Seal 20'
 Placement Method: Pumped Poured
 Seal Type: Neat Cement Cement Grout Concrete Grout

Gravel Packed: Yes No
 From 20 feet to 308 feet

9. WATER LEVEL
 Static water level 196.4 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature _____ °F Quality _____

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor
 Address P.O. Box 5279 Contractor
Elko, NV 89802-5279
 Nevada contractor's license number issued by the State Contractor's Board 0021976
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2084

Signed Vince Hardie
 By driller performing actual drilling on-site or contractor
 Date 10/16/01

BSTL