WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 84781
Permit No.
Basin 61

NOTICE OF INTENT NO. 47556

1. OWNER Barrick Goldstrike Mines PZ99-7
MAILING ADDRESS P.O. Box 29
Elko, NV 89803

ADDRESS AT WELL LOCATION Barrick Goldstrike minesite, north of Carlin, NV

2. LOCATION NW 1/4 NE 1/4 Sec. 19 T 36N N/S R 50E E Eureka County
PERMIT NO. N/A (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Abandoned by pumping neat cement from 559' to surface				
Used 16.5 cu.ft. of neat cement Original Construction Detail:				
Cement		0	33	33
Hole plug		33	272	239
Gravel pack		272	278	6
Hole plug		278	339	61
Gravel pack		339	343	4
Hole plug		343	414	71
Gravel pack		414	419	5
Hole plug		419	533	114
Gravel pack		533	565	32
Hole plug		565	746	181
Gravel pack		746	755	9
Transducers at 275, 340.8, 416.5, 550.9, 749.6.				

Date started 10/3/2001, 19__
Date completed 10/3/2001, 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 755 Feet Depth Cased 559 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
14.75	Inches	0	Feet	35	Feet
7.875	Inches	35	Feet	755	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10.75	34.24	0.250	+2	35
2.375	3.65	0.154	+1	559

Perforations:
Type perforation Slotted
Size perforation 0.125" x 2"
From 539 feet to 559 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 33'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From See Detail feet to feet

9. WATER LEVEL
Static water level Dry feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling (Contractor)
Address P.O. Box 5279 (Contractor)
Elko, NV 89802-5279
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1796
Signed Ron Behrendt (By driller performing actual drilling on-site or contractor)
Date 10/12/01

USE ADDITIONAL SHEETS IF NECESSARY

B.ST.C