WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 84784
Permit No. 55141
Basin 61

NOTICE OF INTENT NO. 47554

1. OWNER Barrick Goldstrike Mines VD97-14
MAILING ADDRESS P.O. Box 29
Elko, NV 89803

ADDRESS AT WELL LOCATION Barrick Goldstrike minesite, north of Carlin, NV

2. LOCATION SW 1/4 NE 1/4 Sec. 19 T 36N N/S R 50E E Eureka County
PERMIT NO. 55141 Issued by Water Resources | N/A Parcel No. | N/A Subdivision Name

3. **WORK PERFORMED**
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. **PROPOSED USE**
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock
Mining

5. **WELL TYPE**
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. **LITHOLOGIC LOG**

Material	Water Strata	From	To	Thickness
Top 20' had been mined off this well. Construction data reflect the original construction.				
Abandoned by pumping abantonite via tremie from 740' to static water level, poured hole plug and abantonite to 20', capped with neat cement.				
Quantities Used:				
Neat cement: 7 cu.ft.				
Hole plug: 17 cu.ft.				
Abantonite: 197 cu.ft.				

Date started 10/5/2001, 19__
Date completed 10/5/2001, 19__

7. **WELL TEST DATA**
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. **WELL CONSTRUCTION**
Depth Drilled 760 Feet Depth Cased 760 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
14.75	Inches	0	Feet	20	Feet
9.875	Inches	20	Feet	760	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
12.625	33.38	0.258	0	20
6.5	17.02	0.250	+1	760

Perforations:
Type perforation Louver
Size perforation 0.125"
From 120 feet to 760 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 103'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 103 feet to 760 feet

9. **WATER LEVEL**
Static water level 433.5 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. **DRILLER'S CERTIFICATION**
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling (Contractor)
Address P.O. Box 5279 (Contractor)
Elko, NV 89802-5279
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1796
Signed Ron Behrendt (By driller performing actual drilling on-site or contractor)
Date 10/12/01

USE ADDITIONAL SHEETS IF NECESSARY

B.ST.L