

OFFICE USE ONLY
 Log No. 85029
 Permit No. _____
 Basin. 70
 NOTICE OF INTENT NO. 96513

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1. OWNER Greyhound Western Inc ADDRESS AT WELL LOCATION Mobaly Ranch Rd
 MAILING ADDRESS Mobaly Ranch Rd
 2. LOCATION SW 1/4 NW 1/4 Sec 28 T. 36 N/S R. 46 E Humboldt County
 PERMIT NO. 63441 Issued by Water Resources Parcel No. _____ Subdivision Name _____

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Topsoil		0	10	10
Sand		10	20	10
Blue Clay		20	30	10
Gravel		30	100	70
Clay Bentonite		100	120	20
Gravel + Clay	<u>yes</u>	120	160	40

8. WELL CONSTRUCTION
 Depth Drilled 160 Feet Depth Cased 160 Feet
 HOLE DIAMETER (BIT SIZE)
 From To
10 5/8 Inches 0 Feet 160 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>6 5/8</u>	<u>10</u>	<u>1 5/8</u>	<u>+</u>	<u>160</u>

Perforations:
 Type perforation Factory cut
 Size perforation 3/32 x 4
 From 140 feet to 160 feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Neat Cement
 Cement Grout
 Concrete Grout
 Depth of Seal 100
 Placement Method: Pumped Poured
 Gravel Packed: Yes No
 From 100 feet to 160 feet

9. WATER LEVEL
 Static water level: 23' feet below land surface
 Artesian flow: N/A G.P.M. N/A P.S.I.
 Water temperature: 60 °F Quality: Good

Date started July 17 2001
 Date completed July 20 2001

7. WELL TEST DATA

TEST METHOD: <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift			
G.P.M.	Draw Down (Feet Below Static)	Time (Hours)	
		<u>4</u>	

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Fred Anderson Drilling Contractor
 Address 10760 Grass Valley Rd Contractor
Winn NV 89445
 Nevada contractor's license number issued by the State Contractor's Board 021467
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2083
 Signed _____
 By driller performing actual drilling on site or contractor
 Date Aug 17 2001

Well log #'s

87645
87646
87647

R.D. Reynolds Drilling Company
P.O. Box 402
Wells, Nevada 89835
(702)752-3205

March 15, 1993

Tom Gallagher
Nev. Division of Water Resources
123 W Nye Ln.
Carson City, NV 89706

Re: Well Abandonments Floka, Antelope, Golconda 1

Dear Tom Gallagher:

Three wells were abandoned by Reynolds Drilling for the Union Pacific Railroad, locations, descriptions, and methods of abandonment are listed below.

[Redacted] was found to be a 4" cased well 30' deep - static level stood at 78'. casing appears to be deteriorated - unsuccessful attempt was made to pull casing. Seven cast boosters were placed at 10 ft. intervals from the bottom to within 10 ft of the surface and detonated. The charge nearest the surface shredded 4' of casing. I assume the others did also. The hole was then filled with grout.

Basin #028
Humboldt
County

[Redacted]. Found well log describes a 305' 10" dry hole. We cleaned this hole out down to 50' and filled with grout.

Basin #028
Humboldt Co

Golconda 1 site (NE 1/4 Sec. 28, T36 N40) Dug well said to be installed in 1909. The hole measured 14' x 14' square and 20' deep, static water level stood at 11ft. 5". We pulled most of the 3" x 12" redwood timbers out of this hole and filled the hole up with concrete.

Basin #09
Humboldt
County

Sincerely,

R.D. Reynolds Drilling

RDR:lt

Well Driller's
License #1390

John - 150
Golconda 1st hole
see of that Kelvin gets a copy
of this. [Signature]