WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 85332
Permit No.
Basin 85

NOTICE OF INTENT NO 47120

1. OWNER RAPHAEL & NINFA VALENCIA
MAILING ADDRESS 839 Marracco Drive
Sparks, Nevada 89434

ADDRESS AT WELL LOCATION 200 Sortor Ct.
Sparks, Nevada 89436

2. LOCATION NW ¼ NW ¼ Sec 30 T 21N N/S R 21 E Washoe County
PERMIT NO. (Issued by Water Resources) 076-402-20 (Parcel No.) Spanish Springs (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	2	2
Volcanic boulders		2	7	5
Volcanic boulders, some clays		7	30	23
Multi-color sandu clays		30	61	31
Granite sands		61	63	2
Brown sandy clays with gravels		63	131	68
Brown sands		131	135	4
Brown sandy clays		135	155	20
Weathered granite		155	253	98
Weathered soft granite with clay streaks		253	321	68
Weathered granite		321	360	39
Fracture(NO WATER)		360	362	2
Weather granite		362	398	36
Fracture granite	X	398	407	9
Weathered granite		407	430	23

Date started September 26, 2001, 19
Date completed October 3, 2001, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30		

8. WELL CONSTRUCTION
Depth Drilled 430 Feet Depth Cased 430 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12 3/4 Inches	0 Feet	30 Feet
10 Inches	30 Feet	50 Feet
8 5/8 Inches	50 Feet	430 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	430

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 385 feet to 425 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50 feet
Placement Method: [ ] Pumped [X] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 430 feet

9. WATER LEVEL
Static water level 255 feet below land surface
Artesian flow G.P.M. 30 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed (By driller performing actual drilling on site or contractor)
Date October 5, 2001

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627