WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 85375
Permit No.
Basin 129

NOTICE OF INTENT NO. 8053

1. OWNER Coeur Rochester
MAILING ADDRESS P.O. Box 1057
Lovelock, NV 89419

ADDRESS AT WELL LOCATION Coeur Rochester minesite, NE of Lovelock, NV.

2. LOCATION SW 1/4 SE 1/4 Sec. 15 T 28N N/S R 34E E Pershing County

PERMIT NO. M/O-1219 (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. **WORK PERFORMED**
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. **PROPOSED USE**
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. **WELL TYPE**
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. **LITHOLOGIC LOG**

Material	Water Strata	From	To	Thickness
Abandoned by pumping neat cement from T.D. to surface.				
Used 15.34 cu.ft. of neat cement.				
Note: We probed this well to 620' prior to abandoning it. This accounts for the excessive volume used. Our client had no record of a monitor well in this area constructed to a 620' depth.				

RECEIVED 01 DEC 21 AM 11:59 STATE ENGINEERS OFFICE

Date started 12/6/2001, 19__
Date completed 12/6/2001, 19__

7. **WELL TEST DATA**

TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. **WELL CONSTRUCTION**

Depth Drilled 450 Feet Depth Cased 450 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6	Inches	0	Feet	25	Feet
5.25	Inches	25	Feet	450	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375		Sch. 80	0	450

Perforations:
Type perforation Slot
Size perforation 0.020"
From 350 feet to 450 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 25'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 345 feet to 450 feet

9. **WATER LEVEL**

Static water level Dry feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. **DRILLER'S CERTIFICATION**

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling (Contractor)
Address P.O. Box 5279 (Contractor)
Elko, NV 89802-5279
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2039
Signed Dennis Robbee
By driller performing actual drilling on-site or contractor
Date 12/18/01

USE ADDITIONAL SHEETS IF NECESSARY

B.STL