WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 85456
Permit No.
Basin 66

NOTICE OF INTENT NO. 42201

1. OWNER Newmont Gold Co.
MAILING ADDRESS PO Box 69
Golconda NV
ADDRESS AT WELL LOCATION Twin Creeks Mine

2. LOCATION SE ¼ SE ¼ Sec. 5 T. 38 ☒ S R. 43 E Humboldt County
PERMIT NO. m/o 793 H (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Ran Tremmy line to 140'				
pumped Abandonite Slurry				
to Surface				

Date started 12-7 2001
Date completed 12-7 2001

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 140' Feet Depth Cased 140' Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5	Sch 80	PVC	0	140'

Perforations:
Type perforation 4.5 Sch 80 PVC Screen
Size perforation 0.020 Slot
From 80 feet to 140' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. WATER LEVEL
Static water level 80 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HARDROCK Exploration Inc (Contractor) 775-738-2926
Address 1000 Barrington Ave (Contractor)
Elko NV
Nevada contractor's license number issued by the State Contractor's Board 0048915
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1670
Signed (By driller performing actual drilling on site or contractor)
Date 12-7-01

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No.
Permit No.
Basin

NOTICE OF INTENT NO. 32772

1. OWNER TWIN CREEKS MINE
MAILING ADDRESS P. O. BOX 69
GOLCONDA, NV 89414

ADDRESS AT WELL LOCATION TWIN CREEKS MINE

2. LOCATION SE¼ SE¼ Sec. 5 T. 38N N/S R. 43 E. HUMBOLDT County
PERMIT NO. M/O-793-H (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
ALLUVIUM - GRAVELS, SANDS & CLAYS		0	140	140

Date started 8/1, 1996
Date completed 8/2, 1996

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
LESS THAN	5	N/A	12

8. WELL CONSTRUCTION
Depth Drilled 140 Feet Depth Cased 140 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12 5/8	Inches	0 Feet	3 Feet
8 3/4	Inches	3 Feet	140 Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5	SCH 80	PVC	+2	80
8 5/8	32	0.30	+3	3

Perforations:
Type perforation 4.5" SCH 80 PVC SCREEN
Size perforation 0.020 SLOT
From 80 feet to 140 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0-50 CEMENT, 50-80 BENTONITE
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 80 feet to 140 feet

9. WATER LEVEL
Static water level 79.6 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature COOL °F Quality CLEAR

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name B & B DRILLING CO., INC. (Contractor)
Address P. O. BOX 2666 (Contractor)
GRAND JUNCTION, CO 81502
Nevada contractor's license number issued by the State Contractor's Board 0030738
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1886
Signed 1711 (By driller performing actual drilling on site or contractor)
Date 9/5/96

USE ADDITIONAL SHEETS IF NECESSARY

RZB 384305-12