WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 85638
Permit No.
Basin 162

NOTICE OF INTENT NO. 21671

1. OWNER Gary Reno
MAILING ADDRESS 601 S. HWY 160 P.O. Box 215, Pahrump, Nv. 89048
ADDRESS AT WELL LOCATION Barnett Street Amargosa Valley Nv. 89020
2. LOCATION SW ¼ NE ¼ Sec. 8 T. 16 N/S R. 49 E N/E County
PERMIT NO. Issued by Water Resources | Parcel No. 19-221-08 | Subdivision Name J+S

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☒ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand		0	4	4
Calegchy		4	7	3
Sand		7	55	48
Compacted gravel		55	60	5
Sand		60	71	11
Compacted gravel		71	74	3
Sand		74	80	6
sandstone		80	90	10
Sand		90	112	22
tan clay		112	120	8
sandy/clay		120	150	30
limestone		150	155	5
sandy clay		155	170	15
limestone		170	175	5
gravel	1st	175	190	15
limestone		190	195	5
Sand & gravel		195	230	35
Sand		230	250	20
Bottom of Hole			250	

DCNR/DWR RECEIVED JAN 09 2002 LAS VEGAS OFFICE

Date started 12/14 2001
Date completed 12/17 2001

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 250 Feet Depth Cased 250 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12½ Inches		0 Feet	250 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	PVC		0	250

Perforations:
Type perforation Machined
Size perforation 3" X 1/8" Every 12"
From 170 feet to 240 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 250 feet

9. WATER LEVEL
Static water level 162 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Cook Drilling Co. (Contractor)
Address HCR 70 Box 543 (Contractor)
Amargosa Valley, Nv. 89020
Nevada contractor's license number issued by the State Contractor's Board 5376-A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2160
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 1/1/02

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627