

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.070 and NAC 534.340

NOTICE OF INTENT NO. 37856

1. OWNER JACK & NORMA WILLIAMS ADDRESS AT WELL LOCATION \_\_\_\_\_  
 MAILING ADDRESS 6310 Potomac Ct. 10355 Adobe Drive  
Sun Valley, Nevada 89433 Reno, Nevada 89506  
 2. LOCATION NW 1/4 NW 1/4 Sec. 13 T. 21N N. 18 E. Washoe COUNTY \_\_\_\_\_  
 PERMIT NO. 087-060-18 Red Rock Area Subdivision Name \_\_\_\_\_  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Sandy brown clay		1	3	2
Brown sand		3	7	4
Sandy brown clays with gravels		7	21	14
Decomposed granite		21	23	2
Brown sandy clays		23	42	19
Brown sand		42	43	1
Sandy brown clays		43	143	100
Soft zone (NO WATER)		143	144	1
Sandy brown clays		144	229	85
Soft zone (app 5 GPM)	X	229	230	1
Sandy brown clays		230	248	18
Soft zone	X	248	260	12
Sandy brown clay		260	268	8
Soft zone	X	268	281	13
Sandy brown clays		281	297	16

8. WELL CONSTRUCTION  
 Depth Drilled 297 Feet Depth Cased 297 Feet  
 HOLE DIAMETER (BIT SIZE)  
 10 Inches From 0 Feet To 50 Feet  
 8 5/8 Inches From 50 Feet To 297 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 CASING SCHEDULE  

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	297

Perforations:  
 Type perforation factory sawed slot  
 Size perforation 3/32 x 3 x 5 around  
 From 230 feet to 250 feet  
 From 270 feet to 290 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 50  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Gravel Packed:  Yes  No  
 From 50 feet to 297 feet

Date started February 11, 2002, 19\_\_\_\_  
 Date completed February 12, 2002, 19\_\_\_\_

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	30		

9. WATER LEVEL  
 Static water level 196 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. 30 P.S.I.  
 Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name WAYNE DRILLING, INC.  
 Address P.O. BOX 12370  
RENO, NEVADA 89510  
 Nevada contractor's license number 0022549  
 issued by the State Contractor's Board  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date February 14, 2002