WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA

DIVISION OF WATER RESOURCES
Monitor Well #S1-31666
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 86385
Permit No.
Basin 72

NOTICE OF INTENT NO. 43486

1. OWNER FLORIDA CANYON MINING, INC.
MAILING ADDRESS P.O. BOX 330
IMLAY, NV 89418

ADDRESS AT WELL LOCATION
HISTORIC STANDARD MINE AREA

2. LOCATION NW NW ¼ Sec. 1 T. 30 N N/S R. 33 E. PERSHING C.
PERMIT NO. M/O 1229 (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
[XX] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [XX] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [XX] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TAN SILTSTONE		0	20	20
SILICIFIED LIMESTONE		20	50	30
TAN SILTSTONE		50	110	60
SILICIFIED LIMESTONE		110	130	20
BLACK TO GRAY LIMESTONE		130	325	195
WATER LEVEL - 263.3 FEET BELOW SURFACE				

Date started DECEMBER 29, 2001, 19
Date completed DECEMBER 29, 2001, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 325 Feet Depth Cased 325 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
5 1/8 Inches	0 Feet	325 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	PVC	SCH 80	+2	325

Perforations:
Type perforation MILL SLOT PVC
Size perforation .020
From 100 feet to 325 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [XX] Yes [ ] No
Depth of Seal 50
Placement Method: [XX] Pumped [ ] Poured

Seal Type: [XX] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [XX] Yes [ ] No
From 100 feet to 325 feet

9. WATER LEVEL
Static water level 263.3 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name DELONG CONSTRUCTION & DRILLING (Contractor)
Address P.O. BOX 907 (Contractor)
WINNEMUCCA, NV 89446
Nevada contractor's license number issued by the State Contractor's Board 0002120C
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 01375
Signed (By driller performing actual drilling on site or contractor)
Date JAN. 14 2002

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627