WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 86659
Permit No.
Basin 212

NOTICE OF INTENT NO. 23365

1. OWNER CLARK COUNTY SANITATION DISTRICT
MAILING ADDRESS
ADDRESS AT WELL LOCATION PROPOSED CROSSING OF LAS VEGAS WASH AND EFFLUENT INTERCEPTOR

2. LOCATION SE ¼ NE ¼ Sec. 15 T. 21 N ⊗ R. 62 E. CLARK County
PERMIT NO. (Issued by Water Resources) 161-15-602-001 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
ALLUVIUM		0	2	2
CLAYEY SAND		2	12	10
CLAYEY SAND WITH GYPSUM		12	14	2
CLAYEY SAND		14	17	3
CLAYEY SAND WITH GRAVEL		17	22	5
GRAVEL WITH SAND AND CLAY		22	24	2
SAND WITH SILT AND CLAY		24	27	3
SAND WITH GRAVEL AND CLAY		27	25	2
SILTY SAND WITH CLAY		25	52	23
GRAVEL WITH SAND AND CLAY		52	69	17
SILTY SAND WITH CLAY		69	79	10
CLAYEY SAND		79	84	5
SILTY SAND WITH CLAY		84	87	3

Date started 6/25/02, 19
Date completed 6/26/02, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 87 Feet Depth Cased 85 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
4.75 Inches		0 Feet	87 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		SCH 40 PVC	0	85

Perforations:
Type perforation FACTORY SLOT
Size perforation 0.020 INCH
From 75 feet to 85 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 67.5
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 67.5 feet to 87 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name CONVERSE CONSULTANTS (Contractor)
Address 731 PILOT ROAD SUITE H (Contractor)
LAS VEGAS, NV 89115
Nevada contractor's license number issued by the State Contractor's Board 48947
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1585
Signed (By driller performing actual drilling on site or contractor)
Date 26 JUNE 2002

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627