

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 51098

1. OWNER Nye County ADDRESS AT WELL LOCATION \_\_\_\_\_  
 MAILING ADDRESS 1210 E. Basin Rd, Suite 6 NC-EWDP-28P  
Pahrump, NV 89066  
 2. LOCATION NW 1/4 SW 1/4 Sec. 29 T. 14 N/S R. 49 E. Nye County  
 PERMIT NO. \_\_\_\_\_ Issued by Water Resources \_\_\_\_\_ Parcel No. \_\_\_\_\_ Subdivision Name \_\_\_\_\_

3. WORK PERFORMED  New Well  Replace  Recondition  Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  Domestic  Irrigation  Test  Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  Cable  Rotary  RVC  Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Alluvium (SW-SM) Qal		0	95	95
Alluvium (SC) Qal		95	155	60
Alluvium (SW-SM) Qal		155	240	85
Rhyolite Tuffs (Timber Mtn. Group Tm)		155	765	610
Rhyolite Tuffs (Paintbrush Group Tp)		765	1145	380
Rhyolite Tuffs (Crater Flat Group Te)		1145	1342	197
Mudstone - Tge		1342	1445	103
Rhyolite Tuffs-Tyo		1445	1974	529
Siltstone -Tge		1974	2080	106

8. WELL CONSTRUCTION  
 Depth Drilled 2080 Feet Depth Cased 460 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 0 To 61 Feet  
 12 Inches 61 Feet  
 6 1/2 Inches 1270 Feet  
 6 1/4 Inches 1270 Feet 1283 Feet  
 5 5/8 CASING SCHEDULE 2080TD  

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	16.9	0.188	0	60 steel
2 3/8	0.95	0.218	0	460 PVC

 Perforations:  
 Type perforation slotted  
 Size perforation 0.020"  
 From 370 feet to 450 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 Surface Seal:  Yes  No Seal Type:  Neat Cement  Cement Grout  Concrete Grout  
 Depth of Seal 360  
 Placement Method:  Pumped  Poured  
 Gravel Packed:  Yes  No Bentonite grout  
 From 360 feet to 452 feet

9. WATER LEVEL  
 Static water level 374 feet below land surface  
 Artesian flow N/A @ 2080 G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature 117 °F Quality good

Date started 10/21, 2002  
 Date completed 11/21, 2002

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Eklund Drilling Company, Inc. Contractor  
 Address P. O. Box 2748 Contractor  
Elko, NV 89803  
 Nevada contractor's license number 0030823 issued by the State Contractor's Board.  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1819M  
 Signed Greg Seerist  
 By driller performing actual drilling on site or contractor  
 Date 12/20/02