WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 87630
Permit No.
Basin 075

NOTICE OF INTENT NO. 33583

1. OWNER BRADY POWER PARTNERS
MAILING ADDRESS P. O. Box 649, Fernley, NV 89408
ADDRESS AT WELL LOCATION 10750 I-80 East, Exit 65, Fernley, NV

2. LOCATION SW ¼ SW ¼ Sec. 1 T. 22N N/X R. 26 E. Churchill County
PERMIT NO. W-467 (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[X] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Tuff and sand		0	1060	1060
Tuff and basalt		1060	1900	840
Tuff, andesite & dacite		1900	3070	1170
Rhyodacite		3070	4435	1365
Tuff		4435	5520	1085
Metavolcanics		5520	6870	1350
Argillite		6870	7037	1670
Redrill #1				
Tuff		2500	3730	1230
Rhyodacite		3730	4420	690
Tuff		4420	5500	1080
Altered Volcanics		5500	5760	260
No samples		5760	5950	190

9-2001

Date started July 14, 19 96
Date completed September 15, 19 96

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [XX] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
1100	260	7.7

8. WELL CONSTRUCTION
Depth Drilled 5950 Feet Depth Cased 5856 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
26 Inches		84 Feet	585 Feet
17.5 Inches		585 Feet	2420 Feet
12.25 Inches		2420 Feet	5950 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
20	94	0.438 K-55	0	566.8
13.375	61	0.430 K-55	0	2409
9.625	40	0.395 K-55	2293	5856

Perforations:
Type perforation slots, 32 per ft.
Size perforation 0.25 x 2.5-inch
From 3920 feet to 4501 feet
From 5183 feet to 5856 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 2409
Placement Method: [XX] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [ ] Yes [X] No
From feet to feet

9. WATER LEVEL
Static water level 275 feet below land surface
Artesian flow 0 G.P.M. P.S.I.
Water temperature +360 °F Quality salty

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Welch & Howell (Contractor)
Address P. O. Box 1851 (Contractor)
El Centro, CA 92244
Nevada contractor's license number issued by the State Contractor's Board XXXXX
Nevada driller's license number issued by the Division of Water Resources, the on-site driller G1483
Signed Joseph D Stalter (By driller performing actual drilling on site or contractor)
Date 9-18-96

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627