WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.3

OFFICE USE ONLY
Log No. 87682
Permit No.
Basin 103

NOTICE OF INTENT NO. 48344

1. OWNER Price Eaves
MAILING ADDRESS PO Box 336, Holt, CA 95234
ADDRESS AT WELL LOCATION #9 Harbor Rd, Dayton, NV 89403

2. LOCATION W 1/2 1/4 SE 1/4 of SW 1/4 Sec 24 T 16 N/S R 21 E/W Lyon County
PERMIT NO. (Issued by Water Resources) Parcel No. 6-112-07 Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SAND + ROCK		0	10	10
BROWN CLAY		10	15	5
BLACK + GREY ROCK		15	75	60
BROWN CLAY		75	95	20
GREEN ROCK		95	100	5
GREEN + BROWN CLAY		100	110	10
BLACK, GREEN, X		110	130	20
RED ROCK				
BROWN CLAY		130	180	50
BROWN CLAY + ROCK		180	200	20
BROWN CLAY		200	230	30
BLACK, BROWN,		230	250	20
GREEN, WHITE ROCK				

RECEIVED 02 SEP 18 AM 11:37 STATE ENGINEER'S OFFICE

Date started JULY 1, 2002
Date completed JULY 8, 2002

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
20		2

8. WELL CONSTRUCTION
Depth Drilled 250 Feet Depth Cased 250 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
10 5/8	0	250

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8"		SCH. 80	10	250
6 5/8"		.188	0	10

Perforations:
Type perforation FACTORY
Size perforation 3/32"
From 230' feet to 250' feet
From feet to feet
From feet to feet
From 110' feet to 130' feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 100'
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 250 feet to 100' feet

9. WATER LEVEL
Static water level 10' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name NEVADA PUMP & DRILLING (Contractor)
Address P.O. BOX 2227 (Contractor)
DAYTON, NV 89403
Nevada contractor's license number issued by the State Contractor's Board 46357
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2187
Signed Thomas Evans (By driller performing actual drilling on site or contractor)
Date 7-15-02

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627