

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
 Log No. 87842
 Permit No. 55139
 Basin 061

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 50857

1. OWNER Barrick Goldstrike Mines BW-10 ADDRESS AT WELL LOCATION Barrick Goldstrike minesite, north of Carlin, NV.
 MAILING ADDRESS P.O. Box 29
Elko, NV 89803

2. LOCATION SE 1/4 SW 1/4 Sec. 24 T 36N N/S R 49E E Eureka County
 PERMIT NO. 55139 Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Well is planned to be mined off to 828' depth.				
Abandonment procedure was reviewed with DWR prior to performing the work.				
Abandoned by pumping abantonite from T.D. to static water level, poured hole plug and abantonite to 395', built a 50' bridge plug of hole plug and neat cement, poured hole plug to 38', and capped with neat cement.				
Quantities Used:				
Cement: 189 cu.ft				
Hole plug: 3,463 cu.ft.				
Abantonite: 724 cu.ft.				

Date started 5/20/2002, 19
 Date completed 5/24/2002, 19

7. WELL TEST DATA

TEST METHOD:	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift		
G.P.M.		

8. WELL CONSTRUCTION

Depth Drilled 2032 Feet Depth Cased 2031 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	To	Feet
<u>42</u>	<u>0</u>	<u>50</u>	<u>Feet</u>
<u>30</u>	<u>53</u>	<u>1593</u>	<u>Feet</u>
<u>19</u>	<u>1593</u>	<u>2032</u>	<u>Feet</u>

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>34</u>	<u>134.7</u>	<u>0.375</u>	<u>0</u>	<u>50</u>
<u>20</u>	<u>78.60</u>	<u>0.375</u>	<u>0</u>	<u>725</u>
<u>20</u>	<u>65.71</u>	<u>0.3125</u>	<u>725</u>	<u>1521</u>

Perforations:

Type perforation Louver
 Size perforation 0.125"

From	To	Feet
<u>495</u>	<u>1521</u>	<u>feet to feet</u>
<u>1509</u>	<u>2031</u>	<u>feet to feet</u>
		<u>feet to feet</u>
		<u>feet to feet</u>

Surface Seal: Yes No
 Depth of Seal 50'
 Placement Method: Pumped Poured
 Seal Type: Neat Cement Cement Grout Concrete Grout
 Gravel Packed: Yes No
 From 0 feet to 1509 feet

9. WATER LEVEL
 Static water level 1865 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature _____ °F Quality _____

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor
 Address P.O. Box 5279 Contractor
Elko, NV 89802-5279
 Nevada contractor's license number issued by the State Contractor's Board 0021976
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1995
 Signed Guadalupe Jacobo
 By driller performing actual drilling on-site or contractor
 Date 5/29/02

BSTL