

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
 Log No. 87843
 Permit No. 67092T
 Basin 0601

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 50856

1. OWNER Barrick Goldstrike Mines VD 96-9 ADDRESS AT WELL LOCATION Barrick Goldstrike minesite, north of Carlin, NV.
 MAILING ADDRESS P.O. Box 29
Elko, NV 89803

2. LOCATION NE 1/4 NE 1/4 Sec. 30 T 36N N/S R 50E E Eureka County
 PERMIT NO. 67092-T Parcel No. N/A Subdivision Name N/A
Issued by Water Resources

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Pump was lost in well during pulling, due to shearing of well at 300', attempted to work tremie past 300', but it would not go deeper.				
Abandoned by pumping neat cement via tremie at 300', poured hole plug (cement would not come up), and capped with 81' of neat cement.				
Could not obtain static water level due to sheared casing.				
Quantities Used:				
Cement: 7.1 cu.ft.				
Hole plug: 193.2 cu.ft.				
Cement: 106.2 cu.ft.				

Date started 5/20/2002, 19
 Date completed 5/20/2002, 19

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

8. WELL CONSTRUCTION
 Depth Drilled 735 Feet Depth Cased 727 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	To	Feet	Feet
<u>14.75</u>	<u>0</u>	<u>22</u>		
<u>7.875</u>	<u>22</u>	<u>735</u>		

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>8.625</u>	<u>22.36</u>	<u>0.250</u>	<u>0</u>	<u>22</u>
<u>4.5</u>	<u>10.79</u>	<u>0.237</u>	<u>+2</u>	<u>727</u>

Perforations:
 Type perforation Mill Slot
 Size perforation 0.125"

From	To	Feet	Feet
<u>105</u>	<u>727</u>		

Surface Seal: Yes No
 Depth of Seal 102'
 Placement Method: Pumped Poured
 Seal Type: Neat Cement Cement Grout Concrete Grout

Gravel Packed: Yes No
 From 104 feet to 735 feet

9. WATER LEVEL
 Static water level Not Measured feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature _____ °F Quality _____

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor
 Address P.O. Box 5279 Contractor
Elko, NV 89802-5279
 Nevada contractor's license number issued by the State Contractor's Board 0021976
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1995

Signed Guadalupe Jacopo
 By driller performing actual drilling on site or contractor
 Date 5/29/02

B.S.L