

STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
 Log No. 87849  
 Permit No. 55150  
 Basin 061

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 50810

1. OWNER Barrick Goldstrike Mines PPW-76 ADDRESS AT WELL LOCATION Barrick GOLDstrike minesite, north of Carlin, NV.  
 MAILING ADDRESS P.O. Box 29  
Elko, NV 89803

2. LOCATION SW 1/4 NE 1/4 Sec. 30 T 36N N/S R 50E E Eureka County  
 PERMIT NO. 55150 Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED  
 New Well  Replace  Recondition  Deepen  Abandon  Other  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
<b>Abandoned by pumping abantonite via tremie from 900' to 501', poured hole plug plus abantonite to 50', placed a 10' cement plug, poured hole plug to 20', capped with neat cement.</b>	<u>Upper 100' ALREADY MINED OFF.</u>			
<b>Quantities Used:</b>				
<b>Cement: 4 cu.ft.</b>		<u>0</u>	<u>20</u>	<u>20</u>
<b>Hole plug: 4 cu.ft.</b>		<u>20</u>	<u>40</u>	<u>20</u>
<b>Cement: 5 cu.ft.</b>		<u>40</u>	<u>50</u>	<u>10</u>
<b>Hole plug: 168.5 cu.ft.</b>		<u>50</u>	<u>501</u>	<u>451</u>
<b>Abantonite: 274 cu.ft.</b>		<u>501</u>	<u>900</u>	<u>399</u>

8. WELL CONSTRUCTION

Depth Drilled 1010 Feet Depth Cased 1000 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
<u>19</u> Inches	<u>0</u> Feet	<u>40</u> Feet
<u>13</u> Inches	<u>40</u> Feet	<u>887</u> Feet
<u>12.25</u> Inches	<u>887</u> Feet	<u>1010</u> Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>14</u>	<u>54.57</u>	<u>0.375</u>	<u>0</u>	<u>40</u>
<u>8.625</u>	<u>22.36</u>	<u>0.250</u>	<u>0</u>	<u>1000</u>

Perforations:  
 Type perforation Louver  
 Size perforation 0.125"  
 From 60 feet to 1000 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No  
 Depth of Seal 50'  
 Placement Method:  Pumped  Poured  
 Seal Type:  Neat Cement  Cement Grout  Concrete Grout  
 Gravel Packed:  Yes  No  
 From 50 feet to 1010 feet

9. WATER LEVEL  
 Static water level 501 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor  
 Address P.O. Box 5279 Contractor  
Elko, NV 89802-5279  
 Nevada contractor's license number issued by the State Contractor's Board 0021976  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1995  
 Signed Madalynne Jacoto  
 By driller performing actual drilling on-site or contractor  
 Date 8/2/02

Date started 7/28/2002, 19  
 Date completed 7/28/2002, 19

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

B.S.F.L