

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 47100

1. OWNER RON CROSSLEY ADDRESS AT WELL LOCATION 355 Curnow Canyon Road
 MAILING ADDRESS 1019 Palmwood Drive Reno, Nevada 89510
Sparks, Nevada 89434

2. LOCATION NW 1/4 SE 1/4 Sec 5 T 21N N/S R 21 E Washoe County
 PERMIT NO. 076-190-08 Spanish Springs
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|--|--------------|------|-----|-----------|
| Top soil | | 0 | 1 | 1 |
| Brownsandy clays with decomposed granite | | 1 | 7 | 6 |
| Weathered granite with clay streaks | | 7 | 55 | 48 |
| Weathered granite | | 55 | 105 | 50 |
| Soft zone (rusty) | | 105 | 106 | 1 |
| Weathereda granite (hard) | | 106 | 230 | 124 |
| Weathered granite with clay streaks | | 230 | 236 | 6 |
| Weathered granite | | 236 | 331 | 95 |
| Rusty brown soft granite | | 331 | 340 | 9 |
| Weathered granite | | 340 | 370 | 30 |
| Gray hard granite | | 370 | 498 | 128 |
| Fracture (NO WATER) | | 498 | 499 | 1 |
| Gray granite | | 499 | 574 | 75 |
| Fracture rock | X | 574 | 627 | 53 |
| Gray granite | | 627 | 630 | 3 |
| Fracture granite | X | 630 | 645 | 15 |
| Gray granite | | 645 | 650 | 5 |

8. WELL CONSTRUCTION
 Depth Drilled 650 Feet Depth Cased 650 Feet

HOLE DIAMETER (BIT SIZE)

| From | To |
|---------------------|--------------------------------|
| <u>10</u> Inches | <u>0</u> Feet <u>50</u> Feet |
| <u>8 5/8</u> Inches | <u>50</u> Feet <u>650</u> Feet |
| _____ Inches | _____ Feet _____ Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|------------|
| <u>6 5/8</u> | | <u>.188</u> | <u>0</u> | <u>650</u> |
| _____ | | _____ | _____ | _____ |

Perforations: factory sawed slot
 Type perforation _____
 Size perforation 3/32 x 3 x 5 around

From 585 feet to 645 feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 50 feet Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout

Gravel Packed: Yes No
 From 50 feet to 650 feet

9. WATER LEVEL
 Static water level 390 feet below land surface
 Artesian flow 25+ G.P.M. _____ P.S.I.
 Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510

Nevada contractor's license number 0022549
 issued by the State Contractor's Board

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923

Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date July 1, 2002

Date started June 24, 2002, 19_____
 Date completed June 28, 2002, 19_____

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|------------|-------------------------------|--------------|
| <u>25+</u> | | |
| _____ | | |
| _____ | | |
| _____ | | |

RECEIVED
 JUL 15 2002
 STATE ENGINEER'S OFFICE