WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 67896
Permit No.
Basin 092-A

NOTICE OF INTENT NO. 50409

1. OWNER DIRK CLARK/J&L BUILDERS
MAILING ADDRESS 10900 RED ROCK ROAD
RENO, NEVADA 89506

ADDRESS AT WELL LOCATION 11305 CARLSBAD
RENO, NEVADA 89506

2. LOCATION NW ¼ SE ¼ Sec 24 T 21N N/S R 18 E Washoe County
PERMIT NO. (Issued by Water Resources) 086-213-01 (Parcel No.) Silver Knolls (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Brown sandy clay		1	35	34
Granite sands		35	38	3
Brown sandy clays		38	129	91
Blue clay		129	137	8
Brown sandy clays		137	155	18
Soft sandy clays		155	174	19
Brown clays		174	179	5
Soft zone	X	179	182	3
Brown clays		182	190	8
Soft zone(red sand)	X	190	202	12
Brown clay		202	205	3
Soft zone	X	205	211	6
BRown clay		211	220	9
Soft zone	X	220	239	19
Brown clay		239	245	6

Date started June 18, 2002, 19
Date completed June 19, 2002, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30+		

8. WELL CONSTRUCTION
Depth Drilled 245 Feet Depth Cased 245 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches	0 Feet	50 Feet
8 5/8 Inches	50 Feet	245 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	245

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 200 feet to 240 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50 feet
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 245 feet

9. WATER LEVEL
Static water level 145 feet below land surface
~~Artesian flow~~ 30+ G.P.M. P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510

Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923

Signed [signature] (By driller performing actual drilling on site or contractor)
Date June 20, 2002

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627