WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 87928
Permit No.
Basin 071

NOTICE OF INTENT NO. 50420

1. OWNER RON HAWKINS
MAILING ADDRESS 6364 North Front Road, Livermore, California 94550
ADDRESS AT WELL LOCATION 670 Leventina Canyon Road, Verdi, Nevada 89439

2. LOCATION SE ¼ NW ¼ Sec. 22 T 19N N/S R 18 E Washoe County
PERMIT NO. (Issued by Water Resources) 038-560-23 (Parcel No.) Beli Ranch (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil with boulder		0	2	2
Brown sandy clay		2	20	18
Gray sandy clay		20	31	11
Brown sandy clays		31	65	34
Soft zone (waterbearing)		65	66	1
Brown sandy clays		66	105	39
Dark brown sandy clays		105	117	12
Gray sandy clays		117	130	13
Soft zone	X	130	134	4
Gray sandy clays		134	143	9
Soft zone	X	143	144	1
Gray sandy clays		144	150	6

Date started September 16, 2002, 20
Date completed September 18, 2002, 20

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
90+		

8. WELL CONSTRUCTION
Depth Drilled 150 Feet Depth Cased 150 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	100 Feet
8 5/8 Inches		100 Feet	150 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	150

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 105 feet to 145 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 100 feet
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 100 feet to 150 feet

9. WATER LEVEL
Static water level 62 feet below land surface
Artesian flow G.P.M. 90+ P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed (By driller performing actual drilling on site or contractor)
Date September 20, 2002

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627