MW3-9

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 87947
Permit No.
Basin 072

NOTICE OF INTENT NO. 43499

1. OWNER FLORIDA CANYON MINING, INC.
MAILING ADDRESS P.O. BOX 330
IMLAY, NV 89418

ADDRESS AT WELL LOCATION STANDARD MINE AREA

2. LOCATION SW ¼ NW ¼ Sec. 1 T 31 N N/S R 33 E PERSHING County
PERMIT NO. M/O 1229 B (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
[XX] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [XX] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [XX] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Overburden		0	30	30
Silicified Limestone		30	80	50
Gray Limestone		80	210	130
Orange Limestone Breccia		210	220	10
Gray Limestone		220	260	40
Diabase		260	310	50
Dark Gray Limestone		310	640	330

Water Level: 503 feet below surface

Date started July 30, 2002, 19
Date completed August 1, 2002, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 650 Feet Depth Cased 650 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
5 3/4 Inches	0 Feet	650 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	PVC	Sch.80	+2	650

Perforations:
Type perforation Mill slot PVC
Size perforation .020
From 100 feet to 650 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [XX] Yes [ ] No
Depth of Seal 50
Placement Method: [XX] Pumped [ ] Poured
Seal Type: [XX] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [XX] Yes [ ] No
From 100 feet to 650 feet

9. WATER LEVEL
Static water level 503 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name GEORGE DELONG CONSTRUCTION, INC. (Contractor)
Address P.O. BOX 907 WINNEMUCCA, NV 89446 (Contractor)

Nevada contractor's license number issued by the State Contractor's Board 0002120C
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 01375

Signed (By driller performing actual drilling on site or contractor)
Date 8-02-02

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627