WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 87981
Permit No.
Basin 179

NOTICE OF INTENT NO. 45801

1. OWNER William P. Harker
MAILING ADDRESS 6771 Tiffollo Lane
Las Vegas, Nevada 89156

ADDRESS AT WELL LOCATION Corner of 212 N. & 21st West

2. LOCATION NE ¼ NW ¼ Sec. 22 T. 17 N/S R. 63 E. White Pine County County
PERMIT NO. Issued by Water Resources: Lot 184 | Parcel No.: APN 05-591-55 | Subdivision Name: Cross Timbers

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	2	2
Course Gravel		2	10	8
Sand & Gravel		10	40	30
Course Sand & Gravel		40	55	15
Sand & Gravel		55	73	18
Water Bearing Sand &	X	73		
Gravel			80	7
Brown Clay		80	90	10
Sand & Gravel with		90		
Clay Stringers			110	20
Brown Clay		110	120	10
Water Bearing Sand	X	120		
& Gravel			140	20
White Clay & Gravel		140	150	10
White Clay		150	160	10

02 JUN 20 PM 12:19
STATE ENGINEER'S OFFICE

Date started May 29, 19 2002
Date completed June 5, 19 2002

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
45	82	1

8. WELL CONSTRUCTION
Depth Drilled 160 Feet Depth Cased 160 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
10-5/8	0	160

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6-5/8	12.92	.188	0	160

Perforations:
Type perforation Factory
Size perforation 1/8" X 2" 6 Rows
From 60 feet to 160 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50 Ft.
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 160 feet

9. WATER LEVEL
Static water level 73 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Christiansen Drilling, Inc. (Contractor)
Address 557 Ely Avenue (Contractor)
Ely, Nevada 89301
Nevada contractor's license number issued by the State Contractor's Board 14790
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1793
Signed Rich Lewis By Jerald D. Christiansen
(By driller performing actual drilling on site or contractor)
Date June 17, 2002

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627