WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 88157
Permit No.
Basin 106

NOTICE OF INTENT NO. 49342

1. OWNER Don Begley
MAILING ADDRESS
ADDRESS AT WELL LOCATION 4055 TOPAZ RANCH Rd

2. LOCATION SW ¼ SW ¼ Sec. 11 T. 10 N/S R. 22 E. Douglas County
PERMIT NO. 1022-11-002-030 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
DIRT-ROCK		0	55	55
BROWN CLAY-ROCK		55	70	15
FRACTURED ROCK	X	70	115	45
BROWN CLAY-ROCK		115	180	65
- BROWN CLAY-GRAVEL	X	180	200	20
BROWN CLAY		200	230	30
- LARGE LAVA ROCK GRAVEL	X	230	245	15
BROWN GRITTY CLAY	X	245	260	15
BROWNISH GREEN CLAY		260	307	47
GREEN FRACTURED ROCK		307	318	11
GREENISH WHITE CLAY		318	325	7
- GREENISH CLAY-FRACTURED ROCK	X	325	340	15
FRACTURED ROCK	X	340	390	50

RECEIVED 2002 OCT -2 PM 4:18 STATE ENGINEER'S OFFICE

Date started 19 Sep 02, ~~20~~
Date completed 24 Sep 02, 20

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
12		1.5

8. WELL CONSTRUCTION
Depth Drilled 390 Feet Depth Cased 390 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	To
9 7/8	0 Feet	340 Feet
6	340 Feet	390 Feet
	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+1	340
5		.188	310	390

Perforations:
Type perforation Factory milled (EM) / TORCH cut (TC)
Size perforation 3/32" X 3"
From 180 feet to 200 feet
From 220 feet to 240 feet
From 320 feet to 340 feet
From 350 feet to 390 feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 59 ft
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 59 feet to 340 feet

9. WATER LEVEL
Static water level 182 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature COLD °F Quality CLEAR

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Blain Drilling & Pump Co.
Address P.O. Box 1255
Carson City, NV 89702

Nevada contractor's license number issued by the State Contractor's Board 46498
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2167
Signed Jack Dotson
By driller performing actual drilling on site or contractor
Date

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627