

STATE OF NEVADA
 DIVISION OF WATER RESOURCES

OFFICE USE ONLY
 Log No. 88271
 Permit No. _____
 Basin 137-B

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Page 1 of 2
 NOTICE OF INTENT NO. 50865

1. OWNER Round Mountain Gold Corporation DW-38
 MAILING ADDRESS P.O. Box 480
Round Mountain, NV 89045

ADDRESS AT WELL LOCATION Round Mountain Gold minesite, Round Mountain, NV.

2. LOCATION SW 1/4 NE 1/4 Sec. 30 T 10N
 PERMIT NO. 68669-T Parcel No. N/A
Issued by Water Resources Parcel No.

N/S R 44E E Nye County
 Subdivision Name N/A

3. WORK PERFORMED
 New Well
 Replace
 Recondition
 Deepen
 Abandon
 Other

4. PROPOSED USE
 Domestic
 Municipal/Industrial
 Irrigation
 Monitor
 Test
 Stock

5. WELL TYPE
 Cable
 Rotary
 RVC
 Air
 Other Fld Rvs

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Blasted gray rock		0	45	45
No circulation		45	60	15
Gray rock		60	160	100
Gray and black rock		160	300	140
Gray rock with trace of clay		300		
Gray and red rock with trace of clay		360		
Gray and green rock		380	390	10
Gray clay		390	405	15
Gray and black rock		405	420	15
Gray clay with trace of rock		420		
Gray rock		585	600	15
Gray rock with trace of clay		600		
Fractured gray rock		635	640	5
Gray rock with trace of brown clay		640		
Gray rock and clay		715	865	150
Black and gray rock with trace of white rock		865		
Dark gray and black rock with trace of white rock		960	960	95
Light gray rock		1100	1145	45
Black rock		1145	1150	5

8. WELL CONSTRUCTION
 Depth Drilled 1150 Feet Depth Cased 1140 Feet
 HOLE DIAMETER (BIT SIZE)

	From	To
38 Inches	0	20
26 Inches	20	60
17.5 Inches	60	1150

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
30	118.65	0.375	0	20
20	52.73	0.250	0	60
10	40.48	0.365	+3	1140

Perforations:
 Type perforation Wire Wrapped
 Size perforation 0.080"
 From 500 feet to 1140 feet
 From _____ feet to _____ feet

Surface Seal: Yes No
 Depth of Seal 60'
 Placement Method: Pumped Poured
 Seal Type: Neat Cement Cement Grout Concrete Grout
 Gravel Packed: Yes No
 From 240 feet to 1150 feet

9. WATER LEVEL
 Static water level 303 feet below land surface
 Artesian flow N/A G.P.M. N/A P.S.I.
 Water temperature 132 °F Quality Fair

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lang Exploratory Drilling Contractor
 Address P.O. Box 5279 Contractor
Elko, NV 89802-5279
 Nevada contractor's license number issued by the State Contractor's Board 0021976
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2115
 Signed Dustin Wilcox
 By driller performing actual drilling on-site or contractor
 Date 7/23/02

Continued on next page
 Date started 7/6/2002, 19
 Date completed 7/13/2002, 19

7. WELL TEST DATA

TEST METHOD:	TEST METHOD:	
	G.P.M.	Draw Down (Feet Below Static)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>305</u>	<u>128</u>
Time (Hours)	<u>1 Hour</u>	

B.S.T.C

